

Web Client

Web Clients are one of the ways to deploy Solutions to end users.

Web Client is a browser-based application of which the UI is rendered in the browser using pure HTML, CSS and a bit of JavaScript for event handling and communication with the Servoy Application Server. The business logic of the Solution that is running in the Web Client is executed on the Application Server for security reasons: the code of the business logic is not exposed in the webpage markup.

In This Chapter

- Supported browsers
- Starting Servoy Web Clients
- Browser sessions
- Web Client configuration settings

Supported browsers

The Servoy Web Client runs in the last few versions of all modern browsers, like Mozilla FireFox, Safari, Google Chrome and Internet Explorer.

Internet Explorer support is split, depending on the use of anchors:

- IE7 or higher if anchoring enabled
- IE6 or higher if anchoring is disabled

See [Web Client Settings](#) for more info on enabling/disabling anchors.

Starting Servoy Web Clients

Servoy Web Clients run in a browser and can be started by accessing a URL on the Servoy Application Server.

Web Client Start URL	What is does	Comments
{serverUrl}/servoy-webclient	Opens the "Select Solution" webpage	The "Select Solution" webpage will not list any solutions if solution browsing is disabled, see Solution browsing .
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}	Opens the specified solution	
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}/a/{value}	Opens the specified solution. The argument value is passed into the Solutions onOpen event handler.	
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}/a/{value}/{name1}/{value1}/{name1}/{value2}	The same as the previous scenario, but with additional custom keys for additional arguments	
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}/m/{myMethodName}	Opens the specified solution and executed the specified method after the solution is opened	
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}/m/{myMethodName}/a/{value}	The same as the previous scenario, but specifying a single value to be passed as an argument into the onOpen event handler and deeplink method	
{serverUrl}/servoy-webclient/ss/s/{mySolutionName}/m/{myMethodName}/a/{value}/{name1}/{value1}/{name2}/{value2}	The same as the previous scenario, but with additional custom keys for additional arguments	

Short vs. long syntax

The urls above use the short syntax. Instead of using the short syntax, the following mapping allows using the longer syntax:

- ss > solutions (Web Client only)
- s > solution (Web Client only)
- m > method
- a > argument

Using Query parameters instead of ...

In all examples above, the specification of the key and value can also be done through query parameters, for example:

```
{serverUrl}/servoy-webclient/ss?s={solutionName}&m={methodName}&a={value}&{param1}={value1}&{param2}={value2}
```

Browser sessions

As browsers share session information between all their tabs and windows, it's not possible to run multiple Web Clients hosted from the same application server within the same browser

Web Client configuration settings

Through the Servoy Admin page, several settings are exposed related to Web Clients. These settings can be found on the Servoy Server Home > Web Client Settings. For more information on the specific settings see [Web Client Settings](#)