

dialogs

The Dialogs plugin provides a few convenient functions to quickly show a dialog. It supports the following types of dialogs:

- Error dialog
- Info dialog
- Input dialog
- Question dialog
- Select dialog
- Warning dialog

Currently this plugin is only supported in the Smart Client. [ServoyForge](#) hosts a drop-in replacement for the Dialogs plugin adds support for the same type of Dialogs and this plugin, but then equally supported in both the Smart and Web Client. This Dialogs module can be found [here](#).

Method Summary

- String** [#showErrorDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showInfoDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showInputDialog](#)(dialog_title, msg, [initialValue])
Shows an input dialog where the user can enter data.
- String** [#showQuestionDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showSelectDialog](#)(dialog_title, msg, optionArray/option1, [...option])
Shows a selection dialog, where the user can select an entry from a list of options.
- String** [#showWarningDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.

Method Details

showErrorDialog

String [showErrorDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.

Parameters

dialog_title
msg
[...button]

Returns

String

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showErrorDialog('Title', 'Value
not allowed', 'OK');
```

showInfoDialog

String [showInfoDialog](#)(dialog_title, msg, [...button])
Shows a message dialog with the specified title, message and a customizable set of buttons.

Parameters

dialog_title
msg
[...button]

Returns

String

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showInfoDialog('Title', 'Value not
allowed','OK');
```

showInputDialog

String **showInputDialog**(dialog_title, msg, [initialValue])

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

dialog_title
msg
[initialValue]

Returns

String

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showQuestionDialog

String **showQuestionDialog**(dialog_title, msg, [...button])

Shows a message dialog with the specified title, message and a customizable set of buttons.

Parameters

dialog_title
msg
[...button]

Returns

String

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showQuestionDialog('Title', 'Value
not allowed','OK');
```

showSelectDialog

String **showSelectDialog**(dialog_title, msg, optionArray/option1, [...option])

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

Parameters

dialog_title
msg
optionArray/option1
[...option]

Returns

String

Sample

```
//show select, returns nothing when canceled
var selectedValue = plugins.dialogs.showSelectDialog('Select', 'please
select a name', 'jan', 'johan', 'sebastiaan');
//also possible to pass array with options
//var selectedValue = plugins.dialogs.showSelectDialog('Select', 'please
select a name', new Array('jan', 'johan', 'sebastiaan'));
```

showWarningDialog

String **showWarningDialog**(dialog_title, msg, [...button])

Shows a message dialog with the specified title, message and a customizable set of buttons.

Parameters

dialog_title

msg

[...button]

Returns

String

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showWarningDialog('Title', 'Value
not allowed', 'OK');
```