


Solution

 Nov 13, 2019 11:52

Supported Clients

SmartClient WebClient NGClient MobileClient

Property Summary

Number	firstForm	The first form that loads when a solution is deployed.
String	i18nDataSource	The i18n database server connection and database table that stores the i18n keys for a solution.
Number	loginForm	The name of the login form that loads when a solution is deployed.
String	loginSolutionName	Get the first module that is also a login solution.
String	modulesNames	The list of modules that have been added to a solution.
Boolean	mustAuthenticate	Flag that tells if authentication is needed in order to access the solution.
Number	solutionType	The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only", "Login", "Authenticator", "Pre-import hook module", "Post-import hook module", "Mobile".
Number	styleSheet	The custom CSS used by the solution (a MEDIA lib entry).
Number	textOrientation	The direction that text is displayed.
String	titleText	The menu bar title of a solution.

Event Summary

Boolean	onClose(force)	The method that is executed when a solution closes.
void	onDataBroadcast(dataSource, action, pks, cached)	Method that is executed when data broadcast occurs.
Boolean	onError(ex)	The method that is executed when a solution opens and an error occurs.
void	onOpen(arg, queryParams)	The method that is executed when a solution opens.

Property Details

firstForm

The first form that loads when a solution is deployed.

NOTE: If the Login form is specified, then the firstForm is the first form that will load next after the loginForm.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

i18nDataSource

The i18n database server connection and database table that stores the i18n keys for a solution.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

loginForm

The name of the login form that loads when a solution is deployed.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

loginSolutionName

Get the first module that is also a login solution.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

modulesNames

The list of modules that have been added to a solution.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

mustAuthenticate

Flag that tells if authentication is needed in order to access the solution.

If unchecked, the Smart Client will always require authentication, regardless of this setting.

If checked, authentication is required, and either a provided loginSolution or otherwise the default Servoy login mechanism will be used.

If default Servoy login mechanism is used, the "servoy.webclient.basic.authentication" setting on the Admin Page can be used to enable the use of the standard browser basic authentication.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

solutionType

The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only", "Login", "Authenticator", "Pre-import hook module", "Post-import hook module", "Mobile".

These constants are defined in SolutionMetaData class.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

styleSheet

The custom CSS used by the solution (a MEDIA lib entry). It can reference other media resources (even additional .css through relative '@import' statements).

For NGClient - this CSS will be available directly in the browser.

Returns

[Number](#)

Supported Clients

NGClient

Sample

textOrientation

The direction that text is displayed.

Options include:

```
DEFAULT
left to right
right to left
locale specific
```

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**titleText**

The menu bar title of a solution.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**Event Details****onClose(force)**

The method that is executed when a solution closes. The default is `-none-`.

Parameters

[Boolean](#) force if false then solution close can be stopped by returning false

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onDataBroadcast(dataSource, action, pks, cached)**

Method that is executed when data broadcast occurs. The default is `-none-`.

Parameters

String	dataSource	table data source
Number	action	see SQL_ACTION_TYPES constants
JSDataset	pks	affected primary keys
Boolean	cached	data was cached

Supported Clients

SmartClient,WebClient,NGClient

Sample**onError(ex)**

The method that is executed when a solution opens and an error occurs. The default is `-none-`.

Parameters


[Object](#) ex exception to handle

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**onOpen(arg, queryParams)**

The method that is executed when a solution opens. The default is -none-.

Parameters

String arg startup argument part of the deeplink url with which the Client was started
Object queryParams all query parameters of the deeplink url with which the Client was started

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample