


oauth

 Feb 08, 2020 02:45

Supported Clients

NGClient

Methods Summary

OAuthService	getOAuthService(provider, clientId, clientSecret, scope, state, deeplinkmethod)	Creates an OAuth service that can be used to obtain an access token and access protected data.
OAuthServiceBuilder	serviceBuilder(clientID)	Creates an OAuth service configurator.

Methods Details

getOAuthService(provider, clientId, clientSecret, scope, state, deeplinkmethod)

Creates an OAuth service that can be used to obtain an access token and access protected data. This method will be deprecated in the following versions, the preferred way is `plugins.oauth.serviceBuilder` with a callback function.

Parameters

String provider	an OAuth provider id, see <code>plugins.oauth.OAuthProviders</code>
String clientId	your app id
String clientSecret	your client secret
String scope	configures the OAuth scope. This is only necessary in some APIs (like Microsoft's).
String state	configures the anti forgery session state. This is available in some APIs (like Facebook's).
String deeplinkmethod	the name of a global method, which will get the code returned by the OAuth provider

Returns

[OAuthService](#)

Supported Clients

NGClient

Sample

```
var clientId = "";
var clientSecret = "";
var scope = null;
var state = "secret123337";
var callback = "deeplink";
service = plugins.oauth.getOAuthService(plugins.oauth.OAuthProviders.FACEBOOK, clientId, clientSecret, null, state, callback, null)
application.showURL(service.getAuthorizationURL());

function deeplink(a,args) {
    service.setAccessToken(args.code);
    var response = service.executeGetRequest("https://graph.facebook.com/v2.11/me");
    if (response.getStatusCode() == 200) {
        application.output(response.getBody());
        var json = response.getAsJSON();
        application.output("Name is "+json.name);
    }
    else {
        application.output('ERROR http status '+response.getStatusCode());
    }
}
```

serviceBuilder(clientID)

Creates an OAuth service configurator.

Parameters

[String](#) clientID;

Returns

[OAuthServiceBuilder](#)

Supported Clients

NGClient

Sample

```
plugins.oauth.serviceBuilder("0lqdl50aw...")           //client/application ID
                    .clientSecret("bIk6163KHi...")       //client secret
                    .defaultScope("email")               //ask permission to get
the user email
                    .state("secret123337")              //anti forgery session
state, required by the Facebook api
                    .deeplink("deeplink_method")         //OPTIONAL deeplink method name or
last part of your redirect URL, see docs
                                                            //if
missing, a global method with the name 'deeplink_svy_oauth' will be generated
                    .callback(myFunction, 30)             //see function below, timeout
is 30 seconds
                    .build(plugins.oauth.OAuthProviders.FACEBOOK);

function myFunction(result, auth_outcome) {
if (result)
{
    //SUCCESS
    var service = auth_outcome;
    if (service.getAccessToken() == null) return;
    var response = service.executeGetRequest("https://graph.facebook.com/v2.11/me");
    if (response.getStatusCode() == 200) {
        application.output(response.getBody());
        var json = response.getAsJSON();
        application.output("Name is "+json.name);
    }
    else {
        application.output('ERROR http status '+response.getStatusCode());
    }
}
else {
    //ERROR
    application.output("ERROR "+auth_outcome);//could not get access token, request timed out, etc..
}
}
}
```