

# Part

## Property Summary

	<a href="#">#allowBreakAcrossPageBounds</a>
Boolean	When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.
	<a href="#">#background</a>
String	The background color of the form part.
	<a href="#">#discardRemainderAfterBreak</a>
Boolean	When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.
	<a href="#">#groupbyDataProviderIDs</a>
String	For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders.
	<a href="#">#height</a>
Number	The height of a selected part; specified in pixels.
	<a href="#">#pageBreakAfterOccurrence</a>
Number	A page break will be inserted after a specified number of occurrences of a selected part.
	<a href="#">#pageBreakBefore</a>
Boolean	When set, a page break will be inserted before each occurrence of a selected part.
	<a href="#">#partType</a>
Number	The type of this part.
	<a href="#">#restartPageNumber</a>
Boolean	When set, page numbering will be restarted after each occurrence of a selected part.
	<a href="#">#sinkWhenLast</a>
Boolean	When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

## Property Details

### [allowBreakAcrossPageBounds](#)

When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.

NOTE: Make sure to set this option when you are printing more than one page per record.

### Returns

[Boolean](#)

### [background](#)

The background color of the form part.

NOTE: When no background color has been set, the default background color will be determined by the Look and Feel (LAF) that has been selected in Application Preferences.

### Returns

[String](#)

### [discardRemainderAfterBreak](#)

When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.

### Returns

[Boolean](#)

### [groupbyDataProviderIDs](#)

For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders. The Leading/Trailing Subsummary parts will be displayed once for each resulted group of data.

### Returns

[String](#)

### [height](#)

The height of a selected part; specified in pixels.

This height property is the lowerbound as its ending Y value (0 == top of the form).

### Returns

[Number](#)

### [pageBreakAfterOccurrence](#)

A page break will be inserted after a specified number of occurrences of a selected part.

**Returns**[Number](#)`pageBreakBefore`

When set, a page break will be inserted before each occurrence of a selected part.

**Returns**[Boolean](#)`partType`

The type of this part.

**Returns**[Number](#)`restartPageNumber`

When set, page numbering will be restarted after each occurrence of a selected part.

**Returns**[Boolean](#)`sinkWhenLast`

When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

**Returns**[Boolean](#)