

# dialogs



## Compatibility

This plugin is supported in the Smart Client only

## Method Summary

- String** [#showErrorDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])  
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showInfoDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])  
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showInputDialog](#)(dialog\_title, msg, [initialValue])  
Shows an input dialog where the user can enter data.
- String** [#showQuestionDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])  
Shows a message dialog with the specified title, message and a customizable set of buttons.
- String** [#showSelectDialog](#)(dialog\_title, msg, optionArray/option1, [option2], [optionN])  
Shows a selection dialog, where the user can select an entry from a list of options.
- String** [#showWarningDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])  
Shows a message dialog with the specified title, message and a customizable set of buttons.

## Method Details

[showErrorDialog](#)

**String** [showErrorDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])

Shows a message dialog with the specified title, message and a customizable set of buttons.

### Parameters

dialog\_title

msg

button1

[button2]

[buttonN]

### Returns

**String**

### Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showErrorDialog('Title', 'Value not allowed','OK');
```

[showInfoDialog](#)

**String** [showInfoDialog](#)(dialog\_title, msg, button1, [button2], [buttonN])

Shows a message dialog with the specified title, message and a customizable set of buttons.

### Parameters

dialog\_title

msg

button1

[button2]

[buttonN]

### Returns

**String**

### Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showInfoDialog('Title', 'Value not allowed','OK');
```

[showInputDialog](#)

**String** [showInputDialog](#)(dialog\_title, msg, [initialValue])

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

### Parameters

dialog\_title

msg

[initialValue]

## Returns

[String](#)

## Sample

```
//show input dialog ,returns nothing when canceled  
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

## showQuestionDialog

[String](#) **showQuestionDialog**(dialog\_title, msg, button1, [button2], [buttonN])

Shows a message dialog with the specified title, message and a customizable set of buttons.

## Parameters

dialog\_title

msg

button1

[button2]

[buttonN]

## Returns

[String](#)

## Sample

```
//show dialog  
var thePressedButton = plugins.dialogs.showQuestionDialog('Title', 'Value not allowed','OK');
```

## showSelectDialog

[String](#) **showSelectDialog**(dialog\_title, msg, optionArray/option1, [option2], [optionN])

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

## Parameters

dialog\_title

msg

optionArray/option1

[option2]

[optionN]

## Returns

[String](#)

## Sample

```
//show select,returns nothing when canceled  
var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a  
name','jan','johan','sebastiaan');  
//also possible to pass array with options  
//var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name', new Array  
( 'jan', 'johan', 'sebastiaan' ));
```

## showWarningDialog

[String](#) **showWarningDialog**(dialog\_title, msg, button1, [button2], [buttonN])

Shows a message dialog with the specified title, message and a customizable set of buttons.

## Parameters

dialog\_title

msg

button1

[button2]

[buttonN]

## Returns

[String](#)

## Sample

```
//show dialog  
var thePressedButton = plugins.dialogs.showWarningDialog('Title', 'Value not allowed','OK');
```