

Popup

Method Summery

CheckBox	<code>#addCheckBox([name], [method], [icon], [mnemonic], [enabled], [align])</code> Add the Checkbox at the selected index (starting at 0) or add it at the end (empty).
Menu	<code>#addMenu([name], [menu], [icon], [mnemonic], [enabled], [align])</code> Add the submenu at the selected index (starting at 0) or add it at the end (empty).
MenuItem	<code>#addMenuItem([name], [method], [icon], [mnemonic], [enabled], [align])</code> Add the item at the selected index (starting at 0) or add it at the end (empty).
RadioButton	<code>#addRadioButton([name], [method], [icon], [mnemonic], [enabled], [align])</code> Add the Radiobutton at the selected index (starting at 0) or add it at the end (empty).
void	<code>#addRadioGroup()</code> Add a Radiogroup for the Radiobuttons.
void	<code>#addSeparator()</code> Add the separator at the selected index (starting at 0) or add it at the end (empty).
CheckBox	<code>#getCheckBox(index)</code> Get the Checkbox at the selected index (starting at 0).
MenuItem	<code>#getItem(index)</code> Get the item at the selected index (starting at 0).
Number	<code>#getItemCount()</code> Get the number of items in the menu.
Number	<code>#getItemIndexByText(name)</code> Retrieve the index of the item by text.
Menu	<code>#getMenu(index)</code> Get the submenu at the selected index (starting at 0).
RadioButton	<code>#getRadioButton(index)</code> Get the Radiobutton at the selected index (starting at 0).
void	<code>#removeAllItems()</code> Remove all items from the menu.
void	<code>#removeItem(index 1, [index 2-n])</code> Remove the item(s) at the selected index/indices.
void	<code>#show([element], [x], [y])</code> Show the popup below the element or add x an y values relative to the element

Method Details

`addCheckBox`

CheckBox `addCheckBox([name], [method], [icon], [mnemonic], [enabled], [align])`
Add the Checkbox at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[method]
[icon]
[mnemonic]
[enabled]
[align]

Returns

CheckBox

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addMenu

Menu **addMenu**([name], [menu], [icon], [mnemonic], [enabled], [align])

Add the submenu at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[menu]
[icon]
[mnemonic]
[enabled]
[align]

Returns

[Menu](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[addMenuItem](#)

MenuItem **addMenuItem**([name], [method], [icon], [mnemonic], [enabled], [align])

Add the item at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]

[method]

[icon]

[mnemonic]

[enabled]

[align]

Returns

[MenuItem](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[addRadioButton](#)

RadioButton **addRadioButton**([name], [method], [icon], [mnemonic], [enabled], [align])

Add the Radiobutton at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]

[method]

[icon]

[mnemonic]

[enabled]

[align]

Returns

[RadioButton](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addRadioGroup

void **addRadioGroup()**

Add a Radiogroup for the Radiobuttons.

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addSeparator

void **addSeparator()**

Add the separator at the selected index (starting at 0) or add it at the end (empty).

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getCheckBox](#)

[CheckBox](#) **getCheckBox**(index)

Get the Checkbox at the selected index (starting at 0).

Parameters

index

Returns

[CheckBox](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getItem](#)

[MenuItem](#) **getItem**(index)

Get the item at the selected index (starting at 0).

Parameters

index

Returns

[MenuItem](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getItemCount](#)

[Number](#) **getItemCount()**

Get the number of items in the menu.

Returns

[Number](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getItemIndexByText](#)

[Number](#) **getItemIndexByText(name)**

Retrieve the index of the item by text.

Parameters

name

Returns

[Number](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getMenu](#)

[Menu](#) **getMenu**(index)

Get the submenu at the selected index (starting at 0).

Parameters

index

Returns

[Menu](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[getRadioButton](#)

[RadioButton](#) **getRadioButton**(index)

Get the Radiobutton at the selected index (starting at 0).

Parameters

index

Returns

[RadioButton](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[removeAllItems](#)

void **removeAllItems**()

Remove all items from the menu.

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

removeItem

void **removeItem**(index 1, [index 2-n])

Remove the item(s) at the selected index/indices.

Parameters

index 1

[index 2-n]

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

[show](#)

void **show**([element], [x], [y])

Show the popup below the element or add x and y values relative to the element

Parameters

[element]

[x]

[y]

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuItem1 = popupmenu.addMenuItem('A',myMethod)
var menuItem2 = popupmenu.addRadioButton('B',myMethod)
var menuItem3 = popupmenu.addRadioButton('C',myMethod)
var menuItem4 = popupmenu.addSeparator()
var menuItem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuItem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is
mnemonic-key

menuItem2.setSelected(true);
menuItem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```