MenuBar

Method Summery

Menu	#addMenu([index]) Add the menu at the selected index (starting at 0) or add it at the end (empty).
Menu	#getMenu(index) Get the menu at the selected index (starting at 0).
Number	#getMenuCount() Get the number of (top level) menu's.
Number	#getMenuIndexByText(menuName) Retrieve the index of the item by text.
void	#removeAllMenus() Remove all menus from the menubar.
void	#removeMenu(index 1, [index 2-n]) Remove the menu(s) at the selected index/indices.
void	#reset() Reset the menubar to the default.
void	#setVisible(visible) Show/hide the menu bar
void	#validate() Use this when your add/remove/edit operation won't refresh.

Method Details

addMenu

Menu **addMenu**([index])

Add the menu at the selected index (starting at 0) or add it at the end (empty).

Parameters

[index]

Returns

Menu

Sample

```
// Note: method addMenu only works in the smart client.

// Add the menu at the selected index (starting at 0) or add it at the end (empty).
```

getMenu

Menu **getMenu**(index)

Get the menu at the selected index (starting at 0).

Parameters

index

Returns

Menu

Sample

```
// Note: method getMenu only works in the smart client.

// Get the menu at the selected index (starting at 0).
```

getMenuCount

Number **getMenuCount**()

Get the number of (top level) menu's.

Returns

Number

Sample

```
// Note: method getMenuCount only works in the smart client.

// Get the number of (top level) menu's.
```

getMenuIndexByText

Number **getMenuIndexByText**(menuName)

Retrieve the index of the item by text.

Parameters

menuName

Returns

Number

Sample

```
// Note: method getMenuIndexByText only works in the smart client.

// Retrieve the index of the item by text.
```

removeAllMenus

void **removeAllMenus**()

Remove all menus from the menubar.

Returns

void

Sample

```
// Note: method removeAllMenus only works in the smart client.

// Remove all menus from the menubar.
```

removeMenu

void **removeMenu**(index 1, [index 2-n])

Remove the menu(s) at the selected index/indices.

Parameters

index 1

[index 2-n]

Returns

void

Sample

```
// Note: method removeMenu only works in the smart client.

// Remove the menu(s) at the selected index/indices.
```

reset

void **reset**()

Reset the menubar to the default.

Returns

void

Sample

```
// Note: method reset only works in the smart client.

// Reset the menubar to the default.
```

setVisible

void **setVisible**(visible)

Show/hide the menu bar

Parameters

visible

Returns

void

Sample

```
// Note: method setVisible only works in the smart client.

// Show/hide the menu bar
```

validate

void **validate**()

Use this when your add/remove/edit operation won't refresh.

Returns

void

Sample

```
// Note: method validate only works in the smart client.

// Use this when your add/remove/edit operation won't refresh.
```