

JSTab

Property Summery

| | | |
|----------------|----------------------|---|
| JSForm | #containsForm | The name of the form displayed in the tab. |
| String | #foreground | The foreground color of the tab. |
| JSMedia | #imageMedia | The name of the image Media file used. |
| String | #name | The name of the tab. |
| String | #relationName | The name of the relation that links the form which contains the tab with the form displayed in the tab. |
| String | #text | The text on the tab. |
| String | #toolTipText | The text displayed when hovering over the component with a mouse cursor. |
| Number | #x | The X coordinate of the tab. |
| Number | #y | The Y coordinate of the tab. |

Property Details

containsForm

The name of the form displayed in the tab.

Returns

JSForm

Sample

```
var childForm = solutionModel.newForm('childForm', 'example_data', 'child_table', 'null', false, 400, 300);
var anotherChildForm = solutionModel.newForm('anotherChildForm', 'example_data', 'child_table', 'null', false, 400, 300);
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.containsForm = anotherChildForm;
```

foreground

The foreground color of the tab.

Returns

String

Sample

```
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.foreground = '#FF0000';
```

imageMedia

The name of the image Media file used.

Returns

JSMedia

Sample

```
var bytes = plugins.file.readFile('d:/ball.jpg');
var ballImage = solutionModel.newMedia('ball.jpg', bytes);
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.imageMedia = ballImage;
```

name

The name of the tab.

Returns

String

Sample

```
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.name = 'firstTabRenamed';
```

relationName

The name of the relation that links the form which contains the tab with the form displayed in the tab.

Returns

String

Sample

```
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm);
firstTab.relationName = 'parent_table_to_child_table';
```

text

The text on the tab.

Returns

String

Sample

```
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.text = 'Better Title';
```

toolTipText

The text displayed when hovering over the component with a mouse cursor.

NOTE:

HTML should be used for multi-line tooltips; you can also use any valid HTML tags to format tooltip text. For example:

<html>This includesbolded text and
BLUE text as well.</html>

Returns

String

Sample

```
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.toolTipText = 'Tooltip';
```

x

The X coordinate of the tab. This influences the order in which the tabs are displayed.

The tabs are displayed in increasing order of the X coordinate. If two tabs have the same X coordinate, then they are displayed in increasing order of the Y coordinate.

Returns

Number

Sample

```
// Create two tabs, then make the second one be displayed to the left of the first
// by setting their X coordinates in the needed order.
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.x = 10;
var secondTab = tabs.newTab('secondTab', 'Another Child Form', anotherChildForm);
secondTab.x = 0;
```

y

The Y coordinate of the tab. Together with the X coordinate, this influences the order in which the tabs are displayed. The tabs are displayed in increasing order of the X coordinate, and if two tabs have the same X coordinate, then they are displayed in increasing order of the Y coordinate.

Returns

Number

Sample

```
// Create two tabs, then make the second one be displayed to the left of the first
// by setting their X to the same value and Y coordinates in the needed order.
var firstTab = tabs.newTab('firstTab', 'Child Form', childForm, relation);
firstTab.x = 0;
firstTab.y = 10;
var secondTab = tabs.newTab('secondTab', 'Another Child Form', anotherChildForm);
secondTab.x = 0;
secondTab.y = 0;
```