

# openid

## Return Types

[JSAuthenticateRequest](#) [JSAuthenticateResult](#)

## Method Summary

[JSAuthenticateRequest](#) [createAuthenticateRequest](#)([identifier](#), [callback](#))  
[request](#) Redirect to openID provider to login, callback method will receive answer.

## Method Details

### createAuthenticateRequest

[JSAuthenticateRequest](#) [createAuthenticateRequest](#) ([identifier](#), [callback](#))  
Redirect to openID provider to login, callback method will receive answer.

#### Parameters

[String](#) [identifier](#)  
[Function](#) [callback](#)

#### Returns

[JSAuthenticateRequest](#)

#### Sample

```
var authenticateRequest = plugins.openid.createAuthenticateRequest('https://www.google.com/accounts/o8/id',
openidLoginCallback);
authenticateRequest.addAttributeRequest('email', 'http://axschema.org/contact/email', true);
//see http://www.axschema.org/types/ for more attributes, not all are supported by all providers!
authenticateRequest.execute();

//sample
//function openidLoginCallback(identifier, authenticateResult)
//{
//    var ok = false;
//    if (identifier)
//    {
//        var id = identifier.substring(identifier.lastIndexOf('=')+1)
//        application.output('id:'+id)
//        var email = authenticateResult.getAttributeValue('email')
//        application.output('email:'+email)
//        ok = security.login(email, id, ['Administrators'])
//    }
//    if (!ok)
//    {
//        application.output('Login failed')
//    }
//}
```