

Solution

Event Summary

- Boolean** [#onClose](#)
The method that is executed when a solution closes.
- [#onDataBroadcast](#)
Method that is executed when data broadcast occurs.
- Boolean** [#onError](#)
The method that is executed when a solution opens and an error occurs.
- [#onOpen](#)
The method that is executed when a solution opens.

Property Summary

- Number** [#firstForm](#)
The first form that loads when a solution is deployed.
- String** [#i18nDataSource](#)
The i18n database server connection and database table that stores the i18n keys for a solution.
- Number** [#loginForm](#)
The name of the login form that loads when a solution is deployed.
- String** [#loginSolutionName](#)
Get the first module that is also a login solution.
- String** [#modulesNames](#)
The list of modules that have been added to a solution.
- Boolean** [#mustAuthenticate](#)
Flag that tells if authentication is needed in order to access the solution.
- Number** [#solutionType](#)
The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only" .
- Number** [#textOrientation](#)
The direction that text is displayed.
- String** [#titleText](#)
The menu bar title of a solution.

Event Details

- onClose**
The method that is executed when a solution closes. The default is -none-.
- Parameters**
{**Boolean**} force – if false then solution close can be stopped by returning false
- Returns**
Boolean
- onDataBroadcast**
Method that is executed when data broadcast occurs. The default is -none-.
- Parameters**
{**String**} dataSource – table data source
{**Boolean**} cached – data was cached
- onError**
The method that is executed when a solution opens and an error occurs. The default is -none-.
- Returns**
Boolean
- onOpen**
The method that is executed when a solution opens. The default is -none-.

Property Details

- firstForm**
The first form that loads when a solution is deployed.
- NOTE: If the Login form is specified, then the firstForm is the first form that will load next after the loginForm.
- Returns**
Number
- i18nDataSource**
The i18n database server connection and database table that stores the i18n keys for a solution.

Returns

[String](#)

loginForm

The name of the login form that loads when a solution is deployed.

Returns

[Number](#)

loginSolutionName

Get the first module that is also a login solution.

Returns

[String](#)

modulesNames

The list of modules that have been added to a solution.

Returns

[String](#)

mustAuthenticate

Flag that tells if authentication is needed in order to access the solution.

To enforce a default Servoy user name and password login dialog; if set a login dialog is required, if unchecked no login dialog is required.

Returns

[Boolean](#)

solutionType

The type of a solution; can be "Normal" (non-module), "Module", "Web client only", "Smart client only" .

Returns

[Number](#)

textOrientation

The direction that text is displayed.

Options include:

DEFAULT

left to right

right to left

locale specific

Returns

[Number](#)

titleText

The menu bar title of a solution.

Returns

[String](#)