

Response

Method Summary

[String](#) [#getCharset\(\)](#)
Get the charset of the response body.

[byte\[\]](#) [#getMediaData\(\)](#)
Get the content of response as binary data.

[String](#) [#getResponseBody\(\)](#)
Get the content of the response as String.

[String](#) [#getResponseHeaders\(\[headerName\]\)](#)
Gets the headers of the response as name/value arrays.

[Number](#) [#getStatusCode\(\)](#)
Gets the status code of the response, the list of the possible values is in HTTP_STATUS constants.

Method Details

[getCharset](#)

[String](#) **getCharset()**

Get the charset of the response body.

Returns

[String](#)

Sample

```
var charset = response.getCharset();
```

[getMediaData](#)

[byte\[\]](#) **getMediaData()**

Get the content of response as binary data. It also supports gzip-ed content.

Returns

[byte\[\]](#)

Sample

```
var mediaData = response.getMediaData();
```

[getResponseBody](#)

[String](#) **getResponseBody()**

Get the content of the response as String.

Returns

[String](#)

Sample

```
var pageData = response.getResponseBody();
```

[getResponseHeaders](#)

getResponseHeaders([headerName])

Gets the headers of the response as name/value arrays.

Parameters

[headerName]

Sample

```
var allHeaders = response.getResponseHeaders(null);
```

[getStatusCode](#)

[Number](#) **getStatusCode()**

Gets the status code of the response, the list of the possible values is in HTTP_STATUS constants.

Returns

[Number](#)

Sample

```
var status = response.getStatusCode();// compare with HTTP_STATUS constants
```