QBLogicalCondition

Feb 26, 2024 09:05

Supported Clients

SmartClient WebClient NGClient

Property Summary

QBTableClause	parent	Get query builder parent table clause, this may be a query or a join clause.
QBSelect	root	Get query builder parent.

Methods Summary

QBLogicalCondition	add(condition)	Add a condition to the AND or OR condition list.

Property Details

parent

Get query builder parent table clause, this may be a query or a join clause.

Returns

QBTableClause

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.person.createSelect();
        query.where.add(query.joins.person_to_parent.joins.person_to_parent.columns.name.eq('john'))
        foundset.loadRecords(query)
```

root

Get query builder parent.

Returns

QBSelect

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var subquery = datasources.db.example_data.order_details.createSelect();

        var query = datasources.db.example_data.orders.createSelect();
        query.where.add(query
                .or
                        .add(query.columns.order_id.not.isin([1, 2, 3]))

                        .add(query.exists(
                                        subquery.where.add(subquery.columns.orderid.eq(query.columns.order_id)).
root
                        ))
                )

        foundset.loadRecords(query)
```

Methods Details

add(condition)

Add a condition to the AND or OR condition list.

Parameters

QBCondition condition the condition to add

Returns

QBLogicalCondition

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.orders.createSelect();
query.where.add(query.columns.orderdate.isNull)
```