

RuntimeCalendar

Extends

RuntimeComponent

Property Summary

String	<code>#bgcolor</code>	Gets or sets the background color of a field.
String	<code>#border</code>	Gets or sets the border attribute(s) of a specified element.
Boolean	<code>#editable</code>	Gets or sets the editable/read-only state of a field; true - editable; false - read-only.
Boolean	<code>#enabled</code>	Gets or sets the enabled state of a specified field, also known as "grayed".
String	<code>#fgcolor</code>	Gets or sets the foreground color of a field.
String	<code>#font</code>	Gets or sets the font name, style, and size of an element.
String	<code>#format</code>	Gets or sets the display formatting of an element for number and text values; does not affect the actual value stored in the database column.
Boolean	<code>#readOnly</code>	Gets or sets the editable/read-only state of a field; true - read-only; false - editable; ! - the editable/read-only state is inverted (the opposite).
String	<code>#titleText</code>	Gets or sets the title text.
String	<code>#toolTipText</code>	Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element.
Boolean	<code>#transparent</code>	Gets or sets the transparency of an element; true - transparent; false - not transparent.
Boolean	<code>#visible</code>	Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

Method Summary

Number	<code>#getAbsoluteFormLocationY()</code>	Returns the absolute form (designed) Y location.
Object	<code>#getClientProperty(key)</code>	Gets the specified client property for the element based on a key.
String	<code>#getDataProviderID()</code>	Get the data provider this UI element (display) is showing.
Object	<code>#getDesignTimeProperty()</code>	Get a design-time property of an element.
String	<code>#getElementType()</code>	Returns the type of a specified element.
Number	<code>#getHeight()</code>	Returns the height of the current element.
Number	<code>#getLocationX()</code>	Returns the x location of the current element.
Number	<code>#getLocationY()</code>	Returns the y location of the current element.
String	<code>#getName()</code>	Returns the name of an element.
Number	<code>#getWidth()</code>	Returns the width of the current element.
void	<code>#putClientProperty(key, value)</code>	Sets the value for the specified element client property key.
void	<code>#requestFocus()</code>	Request the focus in this element.
void	<code>#requestFocus(mustExecuteOnFocusGainedMethod)</code>	Request the focus in this element.
void	<code>#setLocation(x, y)</code>	Sets the location of an element.
void	<code>#setSize(width, height)</code>	Sets the size of the field.

Property Details

bgcolor

Gets or sets the background color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.

Returns

String

Sample

```
//sets the background color of the field  
forms.customer.elements.customer_id.bgcolor = "#FFFFFF";  
//gets the background color of the field  
var c = forms.customer.elements.customer_id.bgcolor;
```

border

Gets or sets the border attribute(s) of a specified element.

The border attributes:

borderType - EmptyBorder, EtchedBorder, BevelBorder, LineBorder, TitleBorder, MatteBorder, SpecialMatteBorder.

size - (numeric value) for: bottom, left, right, top.

color - (hexadecimal value) for: bottom, left, right, top.

dash pattern - (numeric value) for selected side(s).

rounding radius - (numeric value) for selected side(s).

NOTE: Use the same value(s) and order of attribute(s) from the element design time property "borderType".

Parameters

spec – the border attributes

Returns

String

Sample

```
//sets the border type to "LineBorder"  
//sets a 1 px line width for the bottom and left side of the border  
//sets the hexadecimal color of the border to "#ccffcc"  
forms.customer.elements.customer_id.border = 'LineBorder,1,#ccffcc';
```

editable

Gets or sets the editable/read-only state of a field; true - editable; false - read-only.

NOTE the "!" operator can be used to invert the editable state.

Returns

Boolean

Sample

```
var currentState = forms.customer.elements.customer_id.editable;  
forms.customer.elements.customer_id.editable = !currentState;
```

enabled

Gets or sets the enabled state of a specified field, also known as "grayed".
true - enabled; false - not enabled; ! - the enabled state is inverted (the opposite).

NOTE: A disabled element cannot be selected by clicking the element (or by pressing the TAB key even if this option is supported by the operating system).

NOTE: A label or button element will not disable if the "displayType" design time property for a field is set to HTML_AREA.

NOTE: The disabled "grayed" color is dependent on the LAF set in the Servoy Client Application Preferences. For more information see Preferences: Look And Feel in the Servoy Developer User's Guide.

Returns

Boolean

Sample

```
//gets the enabled state of the field  
var currState = forms.customer.elements.customer_id.enabled;  
  
//sets the enabled state of the field  
forms.customer.elements.customer_id.enabled = !currentState;
```

fgcolor

Gets or sets the foreground color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.

Returns

String

Sample

```
//sets the foreground color of the field  
forms.customer.elements.customer_id.fgcolor = "#000000";  
  
//gets the foreground color of the field  
var c = forms.customer.elements.customer_id.fgcolor;
```

font

Gets or sets the font name, style, and size of an element.

font name - the name of the font family.

style - the type of the font. (plain = 0; bold = 1; italic = 2; bold-italic = 3).

size - the size of the font (in points).

Returns

String

Sample

```
forms.customer.elements.customer_id.font = 'Tahoma,1,11';
```

format

Gets or sets the display formatting of an element for number and text values; does not affect the actual value stored in the database column.

Returns

String

Sample

```
//sets the display formatting of the field  
forms.customer.elements.customer_id.format = '###';  
  
//gets the display formatting of the field  
var format = forms.customer.elements.customer_id.format;
```

readOnly

Gets or sets the editable/read-only state of a field; true - read-only; false - editable; ! - the editable/read-only state is inverted (the opposite).

NOTE: A field set as read-only can be selected by clicking (or pressing the TAB key if this option is supported by the operating system) and the field data can be copied.

Returns

Boolean

Sample

```
//gets the editable/read-only state of the field  
var currentState = forms.customer.elements.customer_id.readOnly;  
  
//sets the editable/read-only state of the field  
forms.customer.elements.customer_id.readOnly = !currentState;
```

titleText

Gets or sets the title text.

Returns

String

Sample

```
var titleText = forms.customer.elements.customer_id.titleText;
```

toolTipText

Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element.

NOTE: HTML should be used for multi-line tooltips; you can also use any valid HTML tags to format tooltip text.

Returns

String

Sample

```
//gets the tooltip text of the element  
var toolTip = forms.customer.elements.customer_id.toolTipText;  
  
//sets the tooltip text of the element  
forms.customer.elements.customer_id.toolTipText = "New tip";  
forms.customer.elements.customer_id.toolTipText = "<html>This includes <b>bolded text</b> and <font  
color='blue'>BLUE</font> text as well.";
```

transparent

Gets or sets the transparency of an element; true - transparent; false - not transparent.

NOTE: transparency can be inverted using ! operator: elements.elementName.transparent = !elements.elementName.transparent;

NOTE: transparency will be mostly used for background color, a transparent element will receive the background of the element "beneath" it, a non transparent one will use its own background color

Returns

Boolean

Sample

```
//gets the transparency of the element  
var currentState = forms.customer.elements.customer_id.transparent;  
  
//sets the transparency of the element  
forms.customer.elements.customer_id.transparent = !currentState;
```

visible

Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

NOTE: The visibility of an element is not persistent; the state of visibility only applies to the current user in his/her current session.

Returns

Boolean

Sample

```
//sets the element as visible  
forms.company.elements.faxBtn.visible = true;  
  
//gets the visibility of the element  
var currentState = forms.company.elements.faxBtn.visible;  
  
//sets the element as not visible when the current state is visible  
forms.company.elements.faxBtn.visible = !currentState;
```

Method Details

getAbsoluteFormLocationY

Number getAbsoluteFormLocationY()

Returns the absolute form (designed) Y location.

Returns

Number – The y location of the form in pixels.

Sample

```
var absolute_y = forms.customer.elements.customer_id.getAbsoluteFormLocationY();
```

getClientProperty

Object getClientProperty(key)

Gets the specified client property for the element based on a key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

{**Object**} key – user interface key (depends on operating system)

Returns

Object – The value of the property for specified key.

Sample

```
var property = forms.customer.elements.customer_id.getClientProperty('ToolTipText');
```

getDataProviderID

String getDataProviderID()

Get the data provider this UI element (display) is showing.

Returns

String – The data provider as String.

Sample

```
forms.customer.elements.customer_id.getDataProviderID();
```

getDesignTimeProperty

Object getDesignTimeProperty()

Get a design-time property of an element.

Returns

Object

Sample

```
var prop = forms.orders.elements.mylabel.getDesignTimeProperty('myprop')
```

getElementType

String getElementType()

Returns the type of a specified element.

Returns

String – The display type of the element as **String**.

Sample

```
var et = forms.customer.elements.customer_id.getElementType();
```

getHeight**Number getHeight()**

Returns the height of the current element.

NOTE: getHeight() can be used with getWidth() to set the size of an element using the setSize function. For example:

```
//returns the width (w) and height (h)  
var w = forms.company.elements.faxBtn.getWidth();  
var h = forms.company.elements.faxBtn.getHeight();  
  
//sets the new size  
forms.company.elements.faxBtn.setSize(w,h);  
  
//sets the new size and adds 1 px to both the width and height  
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

Number – The height of the element in pixels.

Sample

```
var ht = forms.customer.elements.customer_id.getHeight();
```

getLocationX**Number getLocationX()**

Returns the x location of the current element.

NOTE: getLocationX() can be used with getLocationY() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates  
var x = forms.company.elements.faxBtn.getLocationX();  
var y = forms.company.elements.faxBtn.getLocationY();  
  
//sets the new location 10 px to the right; 10 px down from the current location  
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number – The x location of the element in pixels.

Sample

```
var x = forms.customer.elements.customer_id.getLocationX();
```

getLocationY**Number getLocationY()**

Returns the y location of the current element.

NOTE: getLocationY() can be used with getLocationX() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates  
var x = forms.company.elements.faxBtn.getLocationX();  
var y = forms.company.elements.faxBtn.getLocationY();  
  
//sets the new location 10 px to the right; 10 px down from the current location  
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number – The y location of the element in pixels.

Sample

```
var y = forms.customer.elements.customer_id.getLocationY();
```

getName**String getName()**

Returns the name of an element. (may be null as well)

Returns

String – The name of the element.

Sample

```
var name = forms.customer.elements.customer_id.getName();
```

getWidth

Number getWidth()

Returns the width of the current element.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)  
var w = forms.company.elements.faxBtn.getWidth();  
var h = forms.company.elements.faxBtn.getHeight();  
  
//sets the new size  
forms.company.elements.faxBtn.setSize(w,h);  
  
//sets the new size and adds 1 px to both the width and height  
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

Number – The width of the element in pixels.

Sample

```
var w = forms.customer.elements.customer_id.getWidth();
```

putClientProperty

void putClientProperty(key, value)

Sets the value for the specified element client property key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

{Object} key – user interface key (depends on operating system)

{Object} value – a predefined value for the key

Returns

void

Sample

```
forms.customer.elements.customer_id.putClientProperty('ToolTipText', 'some text');
```

requestFocus

void requestFocus()

Request the focus in this element. (Focus is also a text cursor on text components).

Returns

void

Sample

```
//request the focus in this forms.customer.elements.customer_id (focus is also a text cursor on text components)  
forms.customer.elements.customer_id.requestFocus();
```

requestFocus

void requestFocus(mustExecuteOnFocusGainedMethod)

Request the focus in this element. (Focus is also a text cursor on text components).

Parameters

{Boolean} mustExecuteOnFocusGainedMethod – If true will execute onFocusGained method, else will not; default value is true.

Returns

void

Sample

```
//request the focus in this forms.customer.elements.customer_id (focus is also a text cursor on text components), skip on focus gained method call  
forms.customer.elements.customer_id.requestFocus(false);
```

setLocation

void **setLocation**(x, y)

Sets the location of an element. It takes as input the X (horizontal) and Y (vertical) coordinates - starting from the TOP LEFT side of the screen.

NOTE: getLocationX() can be used with getLocationY() to return the current location of an element; then use the X and Y coordinates with the setLocation function to set a new location. For Example:

```
//returns the X and Y coordinates  
var x = forms.company.elements.faxBtn.getLocationX();  
var y = forms.company.elements.faxBtn.getLocationY();
```

```
//sets the new location 10 px to the right; 10 px down from the current location  
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Parameters

{Number} x – the X coordinate of the element in pixels.

{Number} y – the Y coordinate of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setLocation(200,200);
```

setSize

void **setSize**(width, height)

Sets the size of the field. It takes as input the width and the height.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)  
var w = forms.company.elements.faxBtn.getWidth();  
var h = forms.company.elements.faxBtn.getHeight();
```

```
//sets the new size
```

```
forms.company.elements.faxBtn.setSize(w,h);
```

```
//sets the new size and adds 1 px to both the width and height  
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Parameters

{Number} width – the width of the element in pixels.

{Number} height – the height of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setSize(20,30);
```