

# JSFoundSet

A JSFoundset is a scriptable object, it contains record objects defined by its SQL. It does lazy load the PKs and records. Each foundset has its own record set and selected index

## Property Summary

**Boolean #multiSelect**  
Get or set the multiSelect flag of the foundset.

## Method Summary

<b>Boolean</b>	<b>#addFoundSetFilterParam(dataprovider, operator, value)</b> Add a filter parameter that is permanent per user session to limit a specified foundset of records.
<b>Boolean</b>	<b>#addFoundSetFilterParam(dataprovider, operator, value, name)</b> Add a filter parameter that is permanent per user session to limit a specified foundset of records.
<b>void</b>	<b>#clear()</b> Clear the foundset.
<b>Boolean</b>	<b>#deleteAllRecords()</b> Delete all records in foundset, resulting in empty foundset.
<b>Boolean</b>	<b>#deleteRecord()</b> Delete currently selected record(s).
<b>Boolean</b>	<b>#deleteRecord(record)</b> Delete record from foundset.
<b>Boolean</b>	<b>#deleteRecord(index)</b> Delete record with the given index.
<b>JSFoundSet</b>	<b>#duplicateFoundSet()</b> Get a duplicate of the foundset.
<b>Number</b>	<b>#duplicateRecord()</b> Duplicate current record, change selection to new record, place on top.
<b>Number</b>	<b>#duplicateRecord(onTop)</b> Duplicate selected record, change selection to new record.
<b>Number</b>	<b>#duplicateRecord(onTop, changeSelection)</b> Duplicate selected record.
<b>Number</b>	<b>#duplicateRecord(index)</b> Duplicate record at index in the foundset, change selection to new record, place on top.
<b>Number</b>	<b>#duplicateRecord(index, onTop)</b> Duplicate record at index in the foundset, change selection to new record.
<b>Number</b>	<b>#duplicateRecord(index, onTop, changeSelection)</b> Duplicate record at index in the foundset.
<b>Number</b>	<b>#duplicateRecord(index, location)</b> Duplicate record at index in the foundset, change selection to new record.
<b>Number</b>	<b>#duplicateRecord(index, location, changeSelection)</b> Duplicate record at index in the foundset.
<b>Boolean</b>	<b>#find()</b> Set the foundset in find mode.
<b>String</b>	<b>#getCurrentSort()</b> Get the current sort columns.
<b>Object</b>	<b>#getDataProviderValue(dataProviderID)</b> Get a value based on a dataprovider name.
<b>String</b>	<b>#getDataSource()</b> Get the datasource used.
<b>Object[]</b>	<b>#getFoundSetFilterParams()</b> Get the list of previously defined foundset filters.
<b>Object[]</b>	<b>#getFoundSetFilterParams(filterName)</b> Get a previously defined foundset filter, using its given name.
<b>QBSelect</b>	<b>#getQuery()</b> Get the query that the foundset is currently using.
<b>JSRecord</b>	<b>#getRecord(index)</b> Get the record object at the index.
<b>Number</b>	<b>#getRecordIndex(record)</b> Get the record index.
<b>String</b>	<b>#getRelationName()</b> Gets the relation name (null if not a related foundset).
<b>Number</b>	<b>#getSelectedIndex()</b> Get the current record index of the foundset.
<b>Number[]</b>	<b>#getSelectedIndexes()</b> Get the selected records indexes.
<b>JSRecord</b>	<b>#getSelectedRecord()</b> Get the selected record.

**JSRecord[]** `#getSelectedRecords()`  
Get the selected records.

**Number** `#getSize()`  
Get the number of records in this foundset.

**Boolean** `#hasConditions()`  
Check whether the foundset has any conditions from a previous find action.

**void** `#invertRecords()`  
Invert the foundset against all rows of the current table.

**Boolean** `#isInFind()`  
Check if this foundset is in find mode.

**Boolean** `#loadAllRecords()`  
Loads all accessible records from the datasource into the foundset.

**Boolean** `#loadOmittedRecords()`  
Loads the records that are currently omitted as a foundset.

**Boolean** `#loadRecords()`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(foundset)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(dataset)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(querybuilder)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(uuidpk)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(numberpk)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(queryString)`  
Load records with primary key (dataset/number/uuid) or query.

**Boolean** `#loadRecords(queryString, argumentsArray)`  
Load records with primary key (dataset/number/uuid) or query.

**Number** `#newRecord()`  
Create a new record on top of the foundset and change selection to it.

**Number** `#newRecord(onTop)`  
Create a new record in the foundset and change selection to it.

**Number** `#newRecord(onTop, changeSelection)`  
Create a new record in the foundset.

**Number** `#newRecord(index)`  
Create a new record in the foundset and change selection to it.

**Number** `#newRecord(index, changeSelection)`  
Create a new record in the foundset.

**Boolean** `#omitRecord()`  
Omit current record, to be shown with loadOmittedRecords.

**Boolean** `#omitRecord(index)`  
Omit record under the given index, to be shown with loadOmittedRecords.

**void** `#relookup()`  
Perform a relookup for the current records  
Lookups are defined in the dataprovider (columns) auto-enter setting and are normally performed over a relation upon record creation.

**void** `#relookup(index)`  
Perform a relookup for the record under the given index  
Lookups are defined in the dataprovider (columns) auto-enter setting and are normally performed over a relation upon record creation.

**Boolean** `#removeFoundSetFilterParam(name)`  
Remove a named foundset filter.

**Number** `#search()`  
Start the database search and use the results, returns the number of records, make sure you did "find" function first.

**Number** `#search(clearLastResults)`  
Start the database search and use the results, returns the number of records, make sure you did "find" function first.

**Number** `#search(clearLastResults, reduceSearch)`  
Start the database search and use the results, returns the number of records, make sure you did "find" function first.

**Boolean** `#selectRecord(pkid1, [pkid2], [pkidn])`  
Select the record based on pk data.

**void** `#setDataProviderValue(dataProviderID, value)`  
Set a value based on a dataprovider name.

**void** `# setSelectedIndex(index)`  
Set the current record index.

**void** `# setSelectedIndexes(indexes)`  
Set the selected records indexes.

**void** `#sort(sortString)`  
Sorts the foundset based on the given sort string.

**void** `#sort(sortString, defer)`  
Sorts the foundset based on the given sort string.

**void** `#sort(comparator)`  
Sorts the foundset based on the given record comparator function.

**JSFoundSet #unrelate()**  
Create a new unrelated foundset that is a copy of the current foundset.

## Property Details

### multiSelect

Get or set the multiSelect flag of the foundset.

#### Returns

**Boolean**

#### Sample

```
// allow user to select multiple rows.  
forms.customer.foundset.multiSelect = true;
```

## Method Details

### addFoundSetFilterParam

**Boolean addFoundSetFilterParam(dataprovider, operator, value)**

Add a filter parameter that is permanent per user session to limit a specified foundset of records.

Use clear() or loadAllRecords() to make the filter effective.

Multiple filters can be added to the same dataprovider, they will all be applied.

#### Parameters

{String} dataprovider – String column to filter on.

{String} operator – String operator: =, <, >, >=, <=, !=, (NOT) LIKE, (NOT) IN, (NOT) BETWEEN and IS (NOT) NULL

{Object} value – Object filter value (for in array and between an array with 2 elements)

#### Returns

**Boolean** – true if adding the filter succeeded, false otherwise.

#### Sample

```
// Filter a fondset on a dataprovider value.  
// Note that multiple filters can be added to the same dataprovider, they will all be applied.  
  
var success = forms.customer.foundset.addFoundSetFilterParam('customerid', '=', 'BLONP', 'custFilter');  
//possible to add multiple  
forms.customer.foundset.loadAllRecords(); //to make param(s) effective  
// Named filters can be removed using forms.customer.foundset.removeFoundSetFilterParam(filterName)
```

### addFoundSetFilterParam

**Boolean addFoundSetFilterParam(dataprovider, operator, value, name)**

Add a filter parameter that is permanent per user session to limit a specified foundset of records.

Use clear() or loadAllRecords() to make the filter effective.

The filter is removed again using removeFoundSetFilterParam(name).

#### Parameters

{String} dataprovider – String column to filter on.

{String} operator – String operator: =, <, >, >=, <=, !=, (NOT) LIKE, (NOT) IN, (NOT) BETWEEN and IS (NOT) NULL optionally augmented with modifiers "#" (ignore case) or "||=" (or-is-null).

{Object} value – Object filter value (for in array and between an array with 2 elements)

{String} name – String name, used to remove the filter again.

#### Returns

**Boolean** – true if adding the filter succeeded, false otherwise.

#### Sample

```
var success = forms.customer.foundset.addFoundSetFilterParam('customerid', '=', 'BLONP', 'custFilter');  
//possible to add multiple  
// Named filters can be removed using forms.customer.foundset.removeFoundSetFilterParam(filterName)  
  
// you can use modifiers in the operator as well, filter on companies where companyname is null or equals-  
ignore-case 'servoy'  
var ok = forms.customer.foundset.addFoundSetFilterParam('companyname', '#^| |=', 'servoy')  
  
forms.customer.foundset.loadAllRecords(); //to make param(s) effective
```

clear

**void clear()**  
Clear the foundset.

**Returns**

void

**Sample**

```
//Clear the foundset, including searches that may be on it  
forms.customer.foundset.clear();
```

**deleteAllRecords**

**Boolean deleteAllRecords()**

Delete all records in foundset, resulting in empty foundset.

**Returns**

Boolean – boolean true if all records could be deleted.

**Sample**

```
var success = forms.customer.foundset.deleteAllRecords();
```

**deleteRecord**

**Boolean deleteRecord()**

Delete currently selected record(s).

If the foundset is in multiselect mode, all selected records are deleted.

**Returns**

Boolean – boolean true if all records could be deleted.

**Sample**

```
var success = forms.customer.foundset.deleteRecord();  
//can return false incase of related foundset having records and orphans records are not allowed by the relation
```

**deleteRecord**

**Boolean deleteRecord(record)**

Delete record from foundset.

**Parameters**

{JSRecord} record – The record to delete from the foundset.

**Returns**

Boolean – boolean true if record could be deleted.

**Sample**

```
var success = forms.customer.foundset.deleteRecord(rec);  
//can return false incase of related foundset having records and orphans records are not allowed by the relation
```

**deleteRecord**

**Boolean deleteRecord(index)**

Delete record with the given index.

**Parameters**

{Number} index – The index of the record to delete.

**Returns**

Boolean – boolean true if record could be deleted.

**Sample**

```
var success = forms.customer.foundset.deleteRecord(4);  
//can return false incase of related foundset having records and orphans records are not allowed by the relation
```

**duplicateFoundSet**

**JSFoundSet duplicateFoundSet()**

Get a duplicate of the foundset.

**Returns**

JSFoundSet – foundset duplicate.

## Sample

```
var dupFoundset = forms.customer.foundset.duplicateFoundSet();
forms.customer.foundset.find();
//search some fields
var count = forms.customer.foundset.search();
if (count == 0)
{
    plugins.dialogs.showWarningDialog('Alert', 'No records found', 'OK');
    controller.loadRecords(dupFoundset);
}
```

duplicateRecord

### Number **duplicateRecord()**

Duplicate current record, change selection to new record, place on top.

#### Returns

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

### Number **duplicateRecord(onTop)**

Duplicate selected record, change selection to new record.

#### Parameters

{Boolean} onTop – when true the new record is added as the topmost record.

#### Returns

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

### Number **duplicateRecord(onTop, changeSelection)**

Duplicate selected record.

#### Parameters

{Boolean} onTop – when true the new record is added as the topmost record.

{Boolean} changeSelection – when true the selection is changed to the duplicated record.

#### Returns

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

### Number **duplicateRecord(index)**

Duplicate record at index in the foundset, change selection to new record, place on top.

#### Parameters

{Number} index – The index of the record to duplicate; defaults to currently selected index. Ignored if first given parameter is a boolean value.

#### Returns

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

**Number** **duplicateRecord**(index, onTop)

Duplicate record at index in the foundset, change selection to new record.

**Parameters**

{Number} index – The index of the record to duplicate; defaults to currently selected index. Ignored if first given parameter is a boolean value.

{Boolean} onTop – when true the new record is added as the topmost record.

**Returns**

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

**Number** **duplicateRecord**(index, onTop, changeSelection)

Duplicate record at index in the foundset.

**Parameters**

{Number} index – The index of the record to duplicate; defaults to currently selected index. Ignored if first given parameter is a boolean value.

{Boolean} onTop – when true the new record is added as the topmost record.

{Boolean} changeSelection – when true the selection is changed to the duplicated record.

**Returns**

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

**Number** **duplicateRecord**(index, location)

Duplicate record at index in the foundset, change selection to new record.

**Parameters**

{Number} index – The index of the record to duplicate; defaults to currently selected index. Ignored if first given parameter is a boolean value.

{Number} location – the new record is added at specified index

**Returns**

Number – 0 if record was not created or the record index if it was created.

## Sample

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

duplicateRecord

**Number** **duplicateRecord**(index, location, changeSelection)

Duplicate record at index in the foundset.

**Parameters**

{Number} index – The index of the record to duplicate; defaults to currently selected index. Ignored if first given parameter is a boolean value.

{Number} location – the new record is added at specified index

{Boolean} changeSelection – when true the selection is changed to the duplicated record.

**Returns**

**Number** – 0 if record was not created or the record index if it was created.

**Sample**

```
forms.customer.foundset.duplicateRecord();
forms.customer.foundset.duplicateRecord(false); //duplicate the current record, adds at bottom
forms.customer.foundset.duplicateRecord(1,2); //duplicate the first record as second record
//duplicates the record (record index 3), adds on top and selects the record
forms.customer.foundset.duplicateRecord(3,true,true);
```

find

**Boolean find()**

Set the foundset in find mode. (Start a find request), use the "search" function to perform/exit the find.

Before going into find mode, all unsaved records will be saved in the database.

If this fails (due to validation failures or sql errors) or is not allowed (autosave off), the foundset will not go into find mode.

Make sure the operator and the data (value) are part of the string passed to dataprovder (included inside a pair of quotation marks).

Note: always make sure to check the result of the find() method.

When in find mode, columns can be assigned string expressions (including operators) that are evaluated as:

General:

c1||c2 (condition1 or condition2)  
c|format (apply format on condition like 'x|dd-MM-yyyy')  
!c (not condition)  
#c (modify condition, depends on column type)  
^ (is null)  
^= (is null or empty)  
<x (less than value x)  
>x (greater than value x)  
<=x (less than or equals value x)  
>=x (greater than or equals value x)  
x...y (between values x and y, including values)  
x (equals value x)

Number fields:

=x (equals value x)  
^= (is null or zero)

Date fields:

#c (equals value x, entire day)  
now (equals now, date and or time)  
// (equals today)  
today (equals today)

Text fields:

#c (case insensitive condition)  
= x (equals a space and 'x')  
^= (is null or empty)  
%x% (contains 'x')  
%x\_y% (contains 'x' followed by any char and 'y')  
% (contains char '%')  
\_ (contains char '\_')

Related columns can be assigned, they will result in related searches.

For example, "employees\_to\_department.location\_id = headoffice" finds all employees in the specified location).

Searching on related aggregates is supported.

For example, "orders\_to\_details.total\_amount = '>1000'" finds all orders with total order details amount more than 1000.

Arrays can be used for searching a number of values, this will result in an 'IN' condition that will be used in the search.

The values are not restricted to strings but can be any type that matches the column type.

For example, "record.department\_id = [1, 33, 99]"

**Returns**

**Boolean** – true if the foundset is now in find mode, false otherwise.

## Sample

```
if (forms.customer.foundset.find()) //find will fail if autosave is disabled and there are unsaved records
{
    columnTextDataProvider = 'a search value'
    // for numbers you have to make sure to format it correctly so that the decimal point is in your
    locales notation (. or ,)
    columnNumberDataProvider = '>' + utils.numberFormat(anumber, '####.00');
    columnDateDataProvider = '31-12-2010|dd-MM-yyyy'
    forms.customer.foundset.search()
}
```

## getCurrentSort

**String getCurrentSort()**

Get the current sort columns.

### Returns

**String** – String sort columns

## Sample

```
//reverse the current sort

//the original sort "companyName asc, companyContact desc"
//the inversed sort "companyName desc, companyContact asc"
var foundsetSort = foundset.getCurrentSort()
var sortColumns = foundsetSort.split(',')
var newFoundsetSort = ''
for(var i=0; i<sortColumns.length; i++)
{
    var currentSort = sortColumns[i]
    var sortType = currentSort.substring(currentSort.length-3)
    if(sortType.equalsIgnoreCase('asc'))
    {
        newFoundsetSort += currentSort.replace(' asc', ' desc')
    }
    else
    {
        newFoundsetSort += currentSort.replace(' desc', ' asc')
    }
    if(i != sortColumns.length - 1)
    {
        newFoundsetSort += ','
    }
}
foundset.sort(newFoundsetSort)
```

## getDataProviderValue

**Object getDataProviderValue(dataProviderID)**

Get a value based on a dataprovider name.

### Parameters

**{String} dataProviderID** – data provider name

### Returns

**Object** – Object value

## Sample

```
var val = forms.customer.foundset.getDataProviderValue('contact_name');
```

## getDataSource

**String getDataSource()**

Get the datasource used.

The datasource is an url that describes the data source.

### Returns

**String** – String data source.

## Sample

```
var dataSource = forms.customer.foundset.getDataSource();
```

### getFoundSetFilterParams

**Object[][] getFoundSetFilterParams()**

Get the list of previously defined foundset filters.

The result is an array of:

[ tableName, dataprovider, operator, value, name ]

#### Returns

**Object[][]** – Array of filter definitions.

## Sample

```
var params = foundset.getFoundSetFilterParams()
for (var i = 0; params != null && i < params.length; i++)
{
    application.output('FoundSet filter on table ' + params[i][0]+ ': '+ params[i][1]+ '+params[i][2]+ '
'+params[i][3] +(params[i][4] == null ? '[no name]' : '['+params[i][4]+'])')
}
```

### getFoundSetFilterParams

**Object[][] getFoundSetFilterParams(filterName)**

Get a previously defined foundset filter, using its given name.

The result is an array of:

[ tableName, dataprovider, operator, value, name ]

#### Parameters

**{String} filterName** – name of the filter to retrieve.

#### Returns

**Object[][]** – Array of filter definitions.

## Sample

```
var params = foundset.getFoundSetFilterParams()
for (var i = 0; params != null && i < params.length; i++)
{
    application.output('FoundSet filter on table ' + params[i][0]+ ': '+ params[i][1]+ '+params[i][2]+ '
'+params[i][3] +(params[i][4] == null ? '[no name]' : '['+params[i][4]+'])')
}
```

### getQuery

**QBSelect getQuery()**

Get the query that the foundset is currently using.

#### Returns

**QBSelect** – query.

## Sample

```
var q = foundset.getQuery()
q.where.add(q.columns.x.eq(100))
foundset.loadRecords(q);
```

### getRecord

**JSRecord getRecord(index)**

Get the record object at the index.

#### Parameters

**{Number} index** – record index

#### Returns

**JSRecord** – Record record.

## Sample

```
var record = forms.customer.foundset.getRecord(index);
```

### getRecordIndex

**Number getRecordIndex(record)**

Get the record index. Will return -1 if the record can't be found.

**Parameters**

{JSRecord} record – Record

**Returns**

Number – int index.

**Sample**

```
var index = forms.customer.foundset.getRecordIndex(record);
```

getRelationName

**String getRelationName()**

Gets the relation name (null if not a related foundset).

**Returns**

String – String relation name when related.

**Sample**

```
var relName = forms.customer.foundset.getRelationName();
```

getSelectedIndex

**Number getSelectedIndex()**

Get the current record index of the foundset.

**Returns**

Number – int current index (1-based)

**Sample**

```
//gets the current record index in the current foundset  
var current = forms.customer.foundset.getSelectedIndex();  
//sets the next record in the foundset  
forms.customer.foundset.setSelectedIndex(current+1);
```

getSelectedIndexes

**Number[] getSelectedIndexes()**

Get the selected records indexes.

When the founset is in multiSelect mode (see property multiSelect), selection can be a more than 1 index.

**Returns**

Number[] – Array current indexes (1-based)

**Sample**

```
var current = forms.customer.foundset.getSelectedIndexes();  
var newSelection = new Array();  
newSelection[0] = current[0];  
forms.customer.foundset.setSelectedIndexes(newSelection);
```

getSelectedRecord

**JSRecord getSelectedRecord()**

Get the selected record.

**Returns**

JSRecord – Record record.

**Sample**

```
var selectedRecord = forms.customer.foundset.getSelectedRecord();
```

getSelectedRecords

**JSRecord[] getSelectedRecords()**

Get the selected records.

When the founset is in multiSelect mode (see property multiSelect), selection can be a more than 1 record.

**Returns**

JSRecord[] – Array current records.

## Sample

```
var selectedRecords = forms.customer.foundset.getSelectedRecords();
```

getSize

**Number getSize()**

Get the number of records in this foundset.

This is the number of records loaded, note that when looping over a foundset, size() may increase as more records are loaded.

**Returns**

**Number** – int current size.

## Sample

```
var nrRecords = forms.customer.foundset.getSize()

// to loop over foundset, recalculate size for each record
for (var i = 1; i <= forms.customer.foundset.getSize(); i++)
{
    var rec = forms.customer.foundset.getRecord(i);
}
```

hasConditions

**Boolean hasConditions()**

Check whether the foundset has any conditions from a previous find action.

**Returns**

**Boolean** – whether the foundset has find-conditions

## Sample

```
if (forms.customer.foundset.hasConditions())
{
    // foundset had find actions
}
```

invertRecords

**void invertRecords()**

Invert the foundset against all rows of the current table.

All records that are not in the foundset will become the current foundset.

**Returns**

**void**

## Sample

```
forms.customer.foundset.invertRecords();
```

isInFind

**Boolean isInFind()**

Check if this foundset is in find mode.

**Returns**

**Boolean** – boolean is in find mode.

## Sample

```
// Returns true when find was called on this foundset and search has not been called yet
forms.customer.foundset.isInFind();
```

loadAllRecords

**Boolean loadAllRecords()**

Loads all accessible records from the datasource into the foundset.

Filters on the foundset are applied.

Before loading the records, all unsaved records will be saved in the database.

If this fails (due to validation failures or sql errors) or is not allowed (autosave off), records will not be loaded,

**Returns**

**Boolean** – true if records are loaded, false otherwise.

**Sample**

```
forms.customer.foundset.loadAllRecords();
```

**loadOmittedRecords**

**Boolean loadOmittedRecords()**

Loads the records that are currently omitted as a foundset.

Before loading the omitted records, all unsaved records will be saved in the database.

If this fails (due to validation failures or sql errors) or is not allowed (autosave off), omitted records will not be loaded,

**Returns**

**Boolean** – true if records are loaded, false otherwise.

**Sample**

```
forms.customer.foundset.loadOmittedRecords();
```

**loadRecords**

**Boolean loadRecords()**

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

```
foundset.loadRecords();
```

5) to load records in to the form based on a query (also known as 'Form by query')

```
foundset.loadRecords(sqlstring,parameters);
```

limitations/requirements for sqlstring are:

- must start with 'select'

- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')

- can contain '?' which are replaced with values from the array supplied to parameters argument

- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:

- must contain 'from' keyword

- the 'from' must be a comma separated list of table names

- must at least select from the table used in Servoy Form

- cannot contain 'group by', 'having' or 'union'

- all columns must be fully qualified like 'orders.order\_id'

**Returns**

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

loadRecords

**Boolean loadRecords(foundset)**

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

**Parameters**

{JSFoundSet} foundset – The foundset to load records from

**Returns**

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

### loadRecords

**Boolean** **loadRecords**(dataset)

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

### Parameters

{**JSDDataSet**} dataset – pkdataset

### Returns

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

### loadRecords

**Boolean** **loadRecords**(querybuilder)

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

### Parameters

{QBSelect} querybuilder – the query builder

### Returns

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

loadRecords

**Boolean loadRecords(uuidpk)**

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

**Parameters**

{**UUID**} uuidpk – single-column pk value

**Returns**

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

### loadRecords

**Boolean** **loadRecords**(numberpk)

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

### Parameters

{Number} numberpk – single-column pk value

### Returns

**Boolean** – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

### loadRecords

**Boolean** **loadRecords(queryString)**

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

```
foundset.loadRecords();
```

5) to load records in to the form based on a query (also known as 'Form by query')  
foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

- must start with 'select'
- the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')
- can contain '?' which are replaced with values from the array supplied to parameters argument
- if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:
- must contain 'from' keyword
- the 'from' must be a comma separated list of table names
- must at least select from the table used in Servoy Form
- cannot contain 'group by', 'having' or 'union'
- all columns must be fully qualified like 'orders.order\_id'

### Parameters

{String} queryString – select statement

### Returns

Boolean – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

### loadRecords

**Boolean** **loadRecords**(queryString, argumentsArray)

Load records with primary key (dataset/number/uuid) or query.

Load records can be used in 5 different ways

1) to copy foundset data from another foundset  
foundset.loadRecords(fs);

2) to load a primary key dataset, will remove related sort!  
var dataset = databaseManager.getDataSetByQuery(...);  
foundset.loadRecords(dataset);

3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)  
foundset.loadRecords(123);  
foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

4) Use without arguments to reload all last related records again, if for example when searched intabpanel.  
when in find mode, this will reload the records from before the find() call.

foundset.loadRecords();

5) to load records in to the form based on a query (also known as 'Form by query')

foundset.loadRecords(sqlstring,parameters);

limitations/requirements for sqlstring are:

-must start with 'select'  
-the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like 'select a\_id, b\_id,c\_id ...')  
-can contain '?' which are replaced with values from the array supplied to parameters argument  
if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional constraints apply:  
-must contain 'from' keyword  
-the 'from' must be a comma separated list of table names  
-must at least select from the table used in Servoy Form  
-cannot contain 'group by', 'having' or 'union'  
-all columns must be fully qualified like 'orders.order\_id'

### Parameters

{String} queryString – select statement

{Object[]} argumentsArray – arguments to query

### Returns

Boolean – true if successful

## Sample

```
//Load records can be used in 5 different ways
//1) to copy foundset data from another foundset
//forms.customer.foundset.loadRecords(fs);

//2) to load a primary key dataset, will remove related sort!
//var dataset = databaseManager.getDataSetByQuery(...);
// dataset must match the table primary key columns (alphabetically ordered)
//forms.customer.foundset.loadRecords(dataset);

//3) to load a single record by primary key, will remove related sort! (pk should be a number or UUID)
//forms.customer.foundset.loadRecords(123);
//forms.customer.foundset.loadRecords(application.getUUID('6b5e2f5d-047e-45b3-80ee-3a32267b1f20'));

//4) to reload all last related records again, if for example when searched intabpanel
//forms.customer.foundset.loadRecords();

//5) to load records in to the form based on a query (also known as 'Form by query')
//forms.customer.foundset.loadRecords(sqlstring,parameters);
//limitations/requirements for sqlstring are:
//--must start with 'select'
//--the selected columns must be the (Servoy Form) table primary key columns (alphabetically ordered like
'select a_id, b_id,c_id ...')
//--can contain '?' which are replaced with values from the array supplied to parameters argument
//if the sqlstring contains an 'order by' clause, the records will be sorted accordingly and additional
constraints apply:
//--must contain 'from' keyword
//--the 'from' must be a comma separated list of table names
//--must at least select from the table used in Servoy Form
//--cannot contain 'group by', 'having' or 'union'
//--all columns must be fully qualified like 'orders.order_id'
```

## newRecord

### Number newRecord()

Create a new record on top of the foundset and change selection to it. Returns -1 if the record can't be made.

#### Returns

Number – int index of new record.

## Sample

```
// foreign key data is only filled in for equals (=) relation items
var idx = forms.customer.foundset.newRecord(false); // add as last record
// forms.customer.foundset.newRecord(); // adds as first record
// forms.customer.foundset.newRecord(2); //adds as second record
if (idx >= 0) // returned index is -1 in case of failure
{
    forms.customer.foundset.some_column = "some text";
    application.output("added on position " + idx);
    // when adding at the end of the foundset, the returned index
    // corresponds with the size of the foundset
}
```

## newRecord

### Number newRecord(onTop)

Create a new record in the foundset and change selection to it. Returns -1 if the record can't be made.

#### Parameters

{Boolean} onTop – when true the new record is added as the topmost record.

#### Returns

Number – int index of new record.

## Sample

```
// foreign key data is only filled in for equals (=) relation items
var idx = forms.customer(foundset.newRecord(false)); // add as last record
// forms.customer(foundset.newRecord()); // adds as first record
// forms.customer(foundset.newRecord(2)); //adds as second record
if (idx >= 0) // returned index is -1 in case of failure
{
    forms.customer(foundset.some_column = "some text";
    application.output("added on position " + idx);
    // when adding at the end of the foundset, the returned index
    // corresponds with the size of the foundset
}
```

## newRecord

**Number newRecord(onTop, changeSelection)**

Create a new record in the foundset. Returns -1 if the record can't be made.

### Parameters

{Boolean} onTop – when true the new record is added as the topmost record.

{Boolean} changeSelection – when true the selection is changed to the new record.

### Returns

Number – int index of new record.

## Sample

```
// foreign key data is only filled in for equals (=) relation items
var idx = forms.customer(foundset.newRecord(false)); // add as last record
// forms.customer(foundset.newRecord()); // adds as first record
// forms.customer(foundset.newRecord(2)); //adds as second record
if (idx >= 0) // returned index is -1 in case of failure
{
    forms.customer(foundset.some_column = "some text";
    application.output("added on position " + idx);
    // when adding at the end of the foundset, the returned index
    // corresponds with the size of the foundset
}
```

## newRecord

**Number newRecord(index)**

Create a new record in the foundset and change selection to it. Returns -1 if the record can't be made.

### Parameters

{Number} index – the new record is added at specified index.

### Returns

Number – int index of new record.

## Sample

```
// foreign key data is only filled in for equals (=) relation items
var idx = forms.customer(foundset.newRecord(false)); // add as last record
// forms.customer(foundset.newRecord()); // adds as first record
// forms.customer(foundset.newRecord(2)); //adds as second record
if (idx >= 0) // returned index is -1 in case of failure
{
    forms.customer(foundset.some_column = "some text";
    application.output("added on position " + idx);
    // when adding at the end of the foundset, the returned index
    // corresponds with the size of the foundset
}
```

## newRecord

**Number newRecord(index, changeSelection)**

Create a new record in the foundset. Returns -1 if the record can't be made.

### Parameters

{Number} index – the new record is added at specified index.

{Boolean} changeSelection – when true the selection is changed to the new record.

### Returns

Number – int index of new record.

## Sample

```
// foreign key data is only filled in for equals (=) relation items
var idx = forms.customer(foundset.newRecord(false)); // add as last record
// forms.customer(foundset.newRecord()); // adds as first record
// forms.customer(foundset.newRecord(2)); //adds as second record
if (idx >= 0) // returned index is -1 in case of failure
{
    forms.customer(foundset.some_column = "some text";
    application.output("added on position " + idx);
    // when adding at the end of the foundset, the returned index
    // corresponds with the size of the foundset
}
```

## omitRecord

### Boolean **omitRecord()**

Omit current record, to be shown with loadOmittedRecords.

If the foundset is in multiselect mode, all selected records are omitted (when no index parameter is used).

Note: The omitted records list is discarded when these functions are executed: loadAllRecords, loadRecords(dataset), loadRecords(sqlstring), invertRecords()

#### Returns

**Boolean** – boolean true if all records could be omitted.

## Sample

```
var success = forms.customer(foundset.omitRecord());
```

## omitRecord

### Boolean **omitRecord(index)**

Omit record under the given index, to be shown with loadOmittedRecords.

If the foundset is in multiselect mode, all selected records are omitted (when no index parameter is used).

Note: The omitted records list is discarded when these functions are executed: loadAllRecords, loadRecords(dataset), loadRecords(sqlstring), invertRecords()

#### Parameters

**{Number}** index – The index of the record to omit.

#### Returns

**Boolean** – boolean true if all records could be omitted.

## Sample

```
var success = forms.customer(foundset.omitRecord());
```

## relookup

### void **relookup()**

Perform a relookup for the current records

Lookups are defined in the dataprovider (columns) auto-enter setting and are normally performed over a relation upon record creation.

#### Returns

**void**

## Sample

```
forms.customer(foundset.relookup(1));
```

## relookup

### void **relookup(index)**

Perform a relookup for the record under the given index

Lookups are defined in the dataprovider (columns) auto-enter setting and are normally performed over a relation upon record creation.

#### Parameters

**{Number}** index – record index (1-based)

#### Returns

**void**

## Sample

```
forms.customer.foundset.relookup(1);
```

removeFoundSetFilterParam

**Boolean removeFoundSetFilterParam(name)**

Remove a named foundset filter.

Use clear() or loadAllRecords() to make the filter effective.

### Parameters

{String} name – String filter name.

### Returns

**Boolean** – true if removing the filter succeeded, false otherwise.

## Sample

```
var success = forms.customer.foundset.removeFoundSetFilterParam('custFilter');// removes all filters with this name  
forms.customer.foundset.loadAllRecords();//to make param(s) effective
```

search

**Number search()**

Start the database search and use the results, returns the number of records, make sure you did "find" function first.

Clear results from previous searches.

Note: Omitted records are automatically excluded when performing a search - meaning that the foundset result by default will not include omitted records.

### Returns

**Number** – the recordCount

## Sample

```
var recordCount = forms.customer.foundset.search();  
//var recordCount = forms.customer.foundset.search(false,false); //to extend foundset
```

search

**Number search(clearLastResults)**

Start the database search and use the results, returns the number of records, make sure you did "find" function first.

Reduce results from previous searches.

Note: Omitted records are automatically excluded when performing a search - meaning that the foundset result by default will not include omitted records.

### Parameters

{Boolean} clearLastResults – boolean, clear previous search, default true

### Returns

**Number** – the recordCount

## Sample

```
var recordCount = forms.customer.foundset.search();  
//var recordCount = forms.customer.foundset.search(false,false); //to extend foundset
```

search

**Number search(clearLastResults, reduceSearch)**

Start the database search and use the results, returns the number of records, make sure you did "find" function first.

Note: Omitted records are automatically excluded when performing a search - meaning that the foundset result by default will not include omitted records.

### Parameters

{Boolean} clearLastResults – boolean, clear previous search, default true

{Boolean} reduceSearch – boolean, reduce (true) or extend (false) previous search results, default true

### Returns

**Number** – the recordCount

## Sample

```
var recordCount = forms.customer.foundset.search();  
//var recordCount = forms.customer.foundset.search(false,false); //to extend foundset
```

selectRecord

**Boolean selectRecord(pkid1, [pkid2], [pkidn])**

Select the record based on pk data.

Note that if the foundset has not loaded the record with the pk, selectrecord will fail.

In case of a table with a composite key, the pk sequence must match the alphabetical ordering of the pk column names.

**Parameters**

pkid1 – primary key

[pkid2] – second primary key (in case of composite primary key)

[pkidn] – nth primary key

**Returns**

**Boolean** – true if succeeded.

**Sample**

```
forms.customer.foundset.selectRecord(pkid1,pkid2,pkidn); //pks must be alphabetically set! It is also possible to use an array as parameter.
```

**setDataProviderValue**

**void setDataProviderValue(dataProviderID, value)**

Set a value based on a dataprovider name.

**Parameters**

{String} dataProviderID – data provider name

{Object} value – value to set

**Returns**

void

**Sample**

```
forms.customer.foundset.setDataProviderValue('contact_name', 'mycompany');
```

**setSelectedIndex**

**void setSelectedIndex(index)**

Set the current record index.

**Parameters**

{Number} index – index to set (1-based)

**Returns**

void

**Sample**

```
//gets the current record index in the current foundset  
var current = forms.customer.foundset.getSelectedIndex();  
//sets the next record in the foundset  
forms.customer.foundset.setSelectedIndex(current+1);
```

**setSelectedIndexes**

**void setSelectedIndexes(indexes)**

Set the selected records indexes.

**Parameters**

{Object[]} indexes – An array with indexes to set.

**Returns**

void

**Sample**

```
var current = forms.customer.foundset.getSelectedIndexes();  
var newSelection = new Array();  
newSelection[0] = current[0];  
forms.customer.foundset.setSelectedIndexes(newSelection);
```

**sort**

**void sort(sortString)**

Sorts the foundset based on the given sort string.

TIP: You can use the Copy button in the developer Select Sorting Fields dialog to get the needed syntax string for the desired sort fields/order.

**Parameters**

{String} sortString – the specified columns (and sort order)

**Returns**

void

**Sample**

```
forms.customer.foundset.sort('columnA desc,columnB asc');
```

**sort**void **sort**(sortString, defer)

Sorts the foundset based on the given sort string.

TIP: You can use the Copy button in the developer Select Sorting Fields dialog to get the needed syntax string for the desired sort fields/order.

**Parameters**{[String](#)} sortString – the specified columns (and sort order){[Boolean](#)} defer – when true, the "sortString" will be just stored, without performing a query on the database (the actual sorting will be deferred until the next data loading action).**Returns**

void

**Sample**

```
forms.customer.foundset.sort('columnA desc,columnB asc');
```

**sort**void **sort**(comparator)

Sorts the foundset based on the given record comparator function.

The comparator function is called to compare

two records, that are passed as arguments, and

it will return -1/0/1 if the first record is less/equal/greater  
then the second record.**Parameters**{[Function](#)} comparator – record comparator function**Returns**

void

**Sample**

```
forms.customer.foundset.sort(mySortFunction);
```

```
function mySortFunction(r1, r2)
{
    var o = 0;
    if(r1.id < r2.id)
    {
        o = -1;
    }
    else if(r1.id > r2.id)
    {
        o = 1;
    }
    return o;
}
```

**unrelate****JSFoundSet** **unrelate()**

Create a new unrelated foundset that is a copy of the current foundset.

If the current foundset is not related, no copy will made.

**Returns****JSFoundSet** – FoundSet unrelated foundset.**Sample**

```
forms.customer.foundset.unrelate();
```