

ComboBox

Event Summary

	onAction	The method that is executed when the component is clicked.
Boolean	onDataChange	Method that is executed when the data in the component is successfully changed.

Property Summary

String	dataProvider	The dataprovider of the component.
Number	displayType	The type of display used by the field.
Boolean	enabled	The enable state of the component, default true.
String	location	The x and y position of the component, in pixels, separated by a comma.
String	name	The name of the component.
String	styleClass	The name of the style class that should be applied to this component.
String	titleDataProvider	Dataprovider for header text to field component
Boolean	titleDisplaysTags	Flag for header text to field component that enables or disables merging of data inside components using tags (placeholders).
String	titleText	Header text to component
Number	valuelist	The valuelist that is used by this field when displaying data.
Boolean	visible	The visible property of the component, default true.

Event Details

onAction

The method that is executed when the component is clicked.

onDataChange

Method that is executed when the data in the component is successfully changed.

Parameters

oldValue - old value
newValue - new value
{[JSEvent](#)} event - the event that triggered the action

Returns

[Boolean](#)

Property Details

dataProvider

The dataprovider of the component.

Returns

[String](#)

displayType

The type of display used by the field. Can be one of CALENDAR, CHECKS, COMBOBOX, HTML_AREA, IMAGE_MEDIA, PASSWORD, RADIOS, RTF_AREA, TEXT_AREA, TEXT_FIELD, TYPE_AHEAD, LIST_BOX, MULTISELECT_LISTBOX or SPINNER.

Returns

Number

enabled

The enable state of the component, default true.

Returns

Boolean - enabled state

location

The x and y position of the component, in pixels, separated by a comma.

Returns

String

name

The name of the component. Through this name it can also accessed in methods.

Returns

String

styleClass

The name of the style class that should be applied to this component.

When defining style classes for specific component types, their names must be prefixed according to the type of the component. For example in order to define a class names 'fancy' for fields, in the style definition the class must be named 'field.fancy'. If it would be intended for labels, then it would be named 'label.fancy'. When specifying the class name for a component, the prefix is dropped however. Thus the field or the label will have its styleClass property set to 'fancy' only.

Returns

String

titleDataProvider

Dataprovider for header text to field component

Returns

String

titleDisplaysTags

Flag for header text to field component that enables or disables merging of data inside components using tags (placeholders).

Tags (or placeholders) are words surrounded by %% on each side. There are data tags and standard tags. Data tags consist in names of dataproviders surrounded by %%. Standard tags are a set of predefined tags that are made available by the system.

See the "Merging data" section for more details about tags.

The default value of this flag is "false", that is merging of data is disabled by default.

Returns

Boolean

titleText

Header text to component

Returns

String

valuelist

The valuelist that is used by this field when displaying data. Can be used with fields of type CHECKS, COMBOBOX, RADIOS and TYPE_AHEAD.

Returns

Number

visible

The visible property of the component, default true.

Returns

[Boolean](#) - visible property