

HeaderTitle

Property Summary

String	dataProvider The dataprovider of the component.
Boolean	displaysTags Flag that enables or disables merging of data inside components using tags (placeholders).
Boolean	enabled The enable state of the component, default true.
String	format The format that should be applied when displaying data(using dataProviderID) in the label/button.
String	location The x and y position of the component, in pixels, separated by a comma.
String	name The name of the component.
String	text The text that is displayed inside the component.
Boolean	visible The visible property of the component, default true.

Property Details

dataProvider

The dataprovider of the component.

Returns

[String](#)

displaysTags

Flag that enables or disables merging of data inside components using tags (placeholders). Tags (or placeholders) are words surrounded by %%on each side. There are data tags and standard tags. Data tags consist in names of dataproviders surrounded by%%. Standard tags are a set of predefined tags that are made available by the system.

See the "Merging data" section for more details about tags.

The default value of this flag is "false", that is merging of data is disabled by default.

Returns

[Boolean](#)

enabled

The enable state of the component, default true.

Returns

[Boolean](#) - enabled state

format

The format that should be applied when displaying data(using dataProviderID) in the label/button. Some examples are "%#", "dd-MM-yyyy", "MM-dd-yyyy", etc.

Returns

[String](#)

location

The x and y position of the component, in pixels, separated by a comma.

Returns

[String](#)

name

The name of the component. Through this name it can also accessed in methods.

Returns

[String](#)

text

The text that is displayed inside the component.

Returns

[String](#)

visible

The visible property of the component, default true.

Returns

[Boolean](#) - visible property