mobileservice

The Mobile service plugin contains functionality to be used in the RESTFull Mobile Service solution that accompanies a Mobile solution.

As such, the Mobile Service plugin is not accessible in the actual Mobile Solution, but only in the Mobile Service solution

Return Types

OfflineDataDescription

Method Summary

OfflineDataDescription	createOfflineDataDescription()
OfflineDataDescription	createOfflineDataDescription(prefix)
JSFoundSet	createRemoteSearchFoundSet(data)
Array	getRowDescriptions(datasource, pks)
void	performSync(data, version, authenticateResult)

Method Details

createOfflineDataDescription

OfflineDataDescription **createOfflineDataDescription** ()

Returns

OfflineDataDescription

createOfflineDataDescription

OfflineDataDescription **createOfflineDataDescription** (prefix)

Parameters

{String} prefix - specified formname prefix used to retrieve row data from REST wise

Returns

OfflineDataDescription

createRemoteSearchFoundSet

JSFoundSet **createRemoteSearchFoundSet** (data)

Parameters

{Object} data - The data that is given into the offline_data.ws_create method

Returns

JSFoundSet - The FoundSet that is in find mode or null if no FoundSet could be created.

getRowDescriptions

Array **getRowDescriptions** (datasource, pks)

Parameters

{String} datasource - the pks belong to
{Object[]} pks - the array of pks

Returns

Array

performSync

void **performSync** (data, version, authenticateResult)

Parameters

{Object} data - The data package that is given to the offline_data form ws_update method.
{Number} version - The version number that is given to the offline_data form ws_update method.
{Object} authenticateResult - The authenticateResult object that is given to the offline_data form ws_update method. (generated by the offline_data.ws_authenticate)

Returns

void