

# JSRenderEvent

## Method Summary

JSRecord	<a href="#">#getRecord()</a> Returns the record of the element that is being rendered.
Number	<a href="#">#getRecordIndex()</a> Returns the record index of the element that is being rendered.
Renderable	<a href="#">#getRenderable()</a> Returns the element that is being rendered.
Boolean	<a href="#">#hasFocus()</a> Returns whether or not the element that is being rendered has focus.
Boolean	<a href="#">#isRecordSelected()</a> Returns whatever or not the record of the element that is being rendered is selected.

## Method Details

getRecord

JSRecord **getRecord()**

Returns the record of the element that is being rendered.

### Returns

JSRecord – Record of the element that is being rendered

### Sample

```
// type the record returned from the call with JSDoc, fill in the right server/tablename
/** @type {JSRecord<db:/servername/tablename>} */
var record = event.getRecord();
```

getRecordIndex

Number **getRecordIndex()**

Returns the record index of the element that is being rendered.

### Returns

Number – record index of the element that is being rendered

### Sample

```
event.getRecordIndex();
```

getRenderable

Renderable **getRenderable()**

Returns the element that is being rendered.

### Returns

Renderable – Renderable the element that is being rendered

### Sample

```
event.getRenderable();
```

hasFocus

Boolean **hasFocus()**

Returns whether or not the element that is being rendered has focus.

### Returns

Boolean – true if the element that is being rendered has the focus, false otherwise

### Sample

```
event.hasFocus();
```

isRecordSelected

Boolean **isRecordSelected()**

Returns whatever or not the record of the element that is being rendered is selected.

**Returns**

**Boolean** – true if the record of the element that is being rendered is selected

**Sample**

```
event.isRecordSelected()
```