

Globals

Property Summery

Array	#allmethods Get all global script names of the current solution.
Array	#allrelations Get all global relation names of the current solution.
Array	#allvariables Get all global variable names of the current solution.
controller	#currentcontroller Get the controller of the top level form in the currently active dialog.

Property Details

[allmethods](#)

Get all global script names of the current solution.

Returns

[Array](#)

Sample

```
var allMethodNames = globals.allmethods;
application.output("There are " + allMethodNames.length + " global methods.");
for (var i=0; i<allMethodNames.length; i++)
    application.output(allMethodNames[i]);
```

[allrelations](#)

Get all global relation names of the current solution.

Returns

[Array](#)

Sample

```
var allRelationNames = globals.allrelations;
application.output("There are " + allRelationNames.length + " global relations.");
for (var i=0; i<allRelationNames.length; i++)
    application.output(allRelationNames[i]);
```

[allvariables](#)

Get all global variable names of the current solution.

Returns

[Array](#)

Sample

```
var allVarNames = globals.allvariables;
application.output("There are " + allVarNames.length + " global variables.");
for (var i=0; i<allVarNames.length; i++)
    application.output(allVarNames[i]);
```

[currentcontroller](#)

Get the controller of the top level form in the currently active dialog.

Returns

[controller](#)

Sample

```
application.output("Current controller is: " + currentcontroller.getName());
```