

RuntimeForm

 Apr 07, 2024 13:19

Supported Clients

SmartClient WebClient NGClient MobileClient

Property Summary		
RuntimeForm	_super	Provides access to the methods of the parent of this form.
containers	containers	Get an object with the containers of a responsive form.
controller	controller	Get the controller of the form.
elements	elements	Get an array with the elements in the form.
JSFoundSet	foundset	Get the foundset of the form.

Property Details

_super
Provides access to the methods of the parent of this form.

Returns

[RuntimeForm](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

`_super.some_method();`

containers
Get an object with the containers of a responsive form.

Returns

[containers](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

`containers.mycontainer.addStyleClasses("red","blue");`

controller
Get the controller of the form.

Returns

[controller](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

`controller.enabled = !controller.enabled;`

elements
Get an array with the elements in the form.

Returns

[elements](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

```
var elems = elements;
application.output("This form has " + elems.length + " named elements.")
for (var i=0; i<elems.length; i++)
    application.output(elems[i].getName());
```

foundset

Get the foundset of the form.

Returns

[JSFoundSet](#)

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
application.output("selected index in form foundset: " + foundset.getSelectedIndex());
```