

JSStyle



Apr 19, 2024 12:09

Supported Clients

SmartClient WebClient NGClient

Property Summary

[String](#) [text](#) The textual content of the style.

Methods Summary

[String](#) [getName\(\)](#) Gets the name of the style.
[UUID](#) [getUUID\(\)](#) Returns the UUID of the style object

Property Details

text
The textual content of the style.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var st = solutionModel.newStyle('myStyle','form { background-color: yellow; }');
st.text = st.text + 'field { background-color: blue; }';
form.styleName = 'myStyle';
application.output('Style name is: ' + st.getName());
```

Methods Details

getName()
Gets the name of the style.

Returns

[String](#) A String holding the name of the style.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var st = solutionModel.newStyle('myStyle','form { background-color: yellow; }');
st.text = st.text + 'field { background-color: blue; }';
form.styleName = 'myStyle';
application.output('Style name is: ' + st.getName());
```

getUUID()
Returns the UUID of the style object

Returns

[UUID](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var st = solutionModel.newStyle('myStyle','form { background-color: yellow; }');  
application.output(st.getUUID().toString());
```