

mobileservice

The Mobile service plugin contains functionality to be used in the RESTFull Mobile Service solution that accompanies a Mobile solution.

As such, the Mobile Service plugin is not accessible in the actual Mobile Solution, but only in the Mobile Service solution

Return Types

[OfflineDataDescription](#)

Method Summary

OfflineDataDescription	createOfflineDataDescription()
OfflineDataDescription	createOfflineDataDescription(prefix)
JSFoundSet	createRemoteSearchFoundSet(data)
Array	getRowDescriptions(datasource, pks)
void	performSync(data, version, authenticateResult)

Method Details

createOfflineDataDescription

[OfflineDataDescription](#) [createOfflineDataDescription\(\)](#)

Returns

[OfflineDataDescription](#)

createOfflineDataDescription

[OfflineDataDescription](#) [createOfflineDataDescription\(prefix\)](#)

Parameters

{[String](#)} prefix - specified formname prefix used to retrieve row data from REST wise

Returns

[OfflineDataDescription](#)

createRemoteSearchFoundSet

[JSFoundSet](#) [createRemoteSearchFoundSet\(data\)](#)

Parameters

{[Object](#)} data - The data that is given into the offline_data.ws_create method

Returns

[JSFoundSet](#) - The FoundSet that is in find mode or null if no FoundSet could be created.

getRowDescriptions

[Array](#) [getRowDescriptions\(datasource, pks\)](#)

Parameters

{[String](#)} datasource - the pks belong to

{[Object](#)[]} pks - the array of pks

Returns

[Array](#)

performSync

[void](#) [performSync\(data, version, authenticateResult\)](#)

Parameters

{Object} data - The data package that is given to the offline_data form ws_update method.

{Number} version - The version number that is given to the offline_data form ws_update method.

{Object} authenticateResult - The authenticateResult object that is given to the offline_data form ws_update method. (generated by the offline_data.ws_authenticate)

Returns

void