

JSColumn

 Apr 09, 2024 20:01

Supported Clients

SmartClient WebClient NGClient

Constants Summary		
Number	DATABASE_IDENTITY	Constant used when setting or getting the sequence type of columns.
Number	DATABASE_SEQUENCE	Constant used when setting or getting the sequence type of columns.
Number	DATETIME	Constant used when setting or getting the type of columns.
Number	EXCLUDED_COLUMN	Constant used when setting or getting the flags of columns.
Number	INTEGER	Constant used when setting or getting the type of columns.
Number	MEDIA	Constant used when setting or getting the type of columns.
Number	NATIVE_COLUMN	Constant used when setting or getting the flags of columns.
Number	NONE	Constant for column information indicating unset values.
Number	NUMBER	Constant used when setting or getting the type of columns.
Number	PK_COLUMN	Constant used when setting or getting the row identifier type of columns.
Number	ROWID_COLUMN	Constant used when setting or getting the row identifier type of columns.
Number	SERVOY_SEQUENCE	Constant used when setting or getting the sequence type of columns.
Number	TENANT_COLUMN	Constant used when setting or getting the flags of columns.
Number	TEXT	Constant used when setting or getting the type of columns.
Number	UUID_COLUMN	Constant used when setting or getting the flags of columns.
Number	UUID_GENERATOR	Constant used when setting or getting the sequence type of columns.

Methods Summary		
Boolean	getAllowNull()	Get the allow-null flag of the column.
String	getDataProviderID()	Get the data provider id for this column (which is the same as name if not explicitly defined otherwise).
String	getDefaultFormat()	Get the default format of the column.
String	getDescription()	Get the description property of the column.
String	getForeignType()	Get the foreign type of the column.
Number	getLength()	Get the length of the column as reported by the JDBC driver.
String	getName()	Get the name of the column as used by Servoy.
String	getQualifiedName()	Get the qualified name (including table name) of the column as known by the database.
String	getQuotedSQLName()	Returns a quoted version of the column name, if necessary, as defined by the actual database used.
Number	getRowIdentifierType()	Get the row identifier type of the column.
String	getSQLName()	Get the name of the column as known by the database.
Number	getSQLType()	Get the raw JDBC type of the column, which allows to check database specific types, like sting/byte column type variations.
Number	getScale()	Get the scale of the column as reported by the JDBC driver.
Number	getSequenceType()	Get the sequence type of the column.
JSTable	getTable()	Get the JSTable of this column.
String	getTitle()	Get the title property of the column.
Number	getType()	Get the JDBC type of the column.
String	getTypeAsString()	Get the name JDBC type of the column.
Boolean	hasFlag(flag)	Check a flag of the column.

Constants Details

DATABASE_IDENTITY

Constant used when setting or getting the sequence type of columns.

Returns

Number

Supported Clients

SmartClient,WebClient,NGClient

Sample

```

var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}

```

DATABASE_SEQUENCE

Constant used when setting or getting the sequence type of columns.

Returns

[Number](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```

var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}

```

DATETIME

Constant used when setting or getting the type of columns.

Returns

[Number](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```

var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}

```

EXCLUDED_COLUMN

Constant used when setting or getting the flags of columns.
This flag identifies columns that are skipped in the sql.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (column.hasFlag(JSColumn.UUID_COLUMN))
{
    // handle uuid column
}
```

INTEGER

Constant used when setting or getting the type of columns.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}
```

MEDIA

Constant used when setting or getting the type of columns.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}
```

NATIVE_COLUMN

Constant used when setting or getting the flags of columns.

This flag identifies columns that are marked as a native type column (for example uniqueidentifier).

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (column.hasFlag(JSColumn.UUID_COLUMN))
{
    // handle uuid column
}
```

NONE

Constant for column information indicating unset values.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}
```

NUMBER

Constant used when setting or getting the type of columns.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}
```

PK_COLUMN

Constant used when setting or getting the row identifier type of columns.
This value identifies columns that are defined as primary key in the database.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getRowIdentifierType())
{
case JSColumn.NONE:
    // handle normal column
    break;

case JSColumn.PK_COLUMN:
    // handle database pk column
    break;

case JSColumn.ROWID_COLUMN:
    // handle developer defined pk column
    break;
}
```

ROWID_COLUMN

Constant used when setting or getting the row identifier type of columns.

This value identifies columns that are defined as primary key by the developer (but not in the database).

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getRowIdentifierType())
{
case JSColumn.NONE:
    // handle normal column
    break;

case JSColumn.PK_COLUMN:
    // handle database pk column
    break;

case JSColumn.ROWID_COLUMN:
    // handle developer defined pk column
    break;
}
```

SERVOY_SEQUENCE

Constant used when setting or getting the sequence type of columns.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}
```

TENANT_COLUMN

Constant used when setting or getting the flags of columns.
This flag identifies columns that are marked as a tenant column.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (column.hasFlag(JSColumn.UUID_COLUMN))
{
    // handle uuid column
}
```

TEXT

Constant used when setting or getting the type of columns.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}
```

UUID_COLUMN

Constant used when setting or getting the flags of columns.
This flag identifies columns whose values are treated as UUID.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (column.hasFlag(JSColumn.UUID_COLUMN))
{
    // handle uuid column
}
```

UUID_GENERATOR

Constant used when setting or getting the sequence type of columns.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}
```

Methods Details**getAllowNull()**

Get the allow-null flag of the column.

Returns

[Boolean](#) boolean allow-null flag.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (!column.getAllowNull())
{
    // column cannot be null
}
```

getDataProviderID()

Get the data provider id for this column (which is the same as name if not explicitly defined otherwise).

Returns

[String](#) String dataprovider id.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var dataProviderId = column.getDataProviderID()
```

getDefaultFormat()

Get the default format of the column.

Returns

[String](#) String column default format.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var format = column.getDefaultFormat()
```

getDescription()

Get the description property of the column.

Returns

[String](#) String column description.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customername')
var desc = column.getDescription()
```

getForeignType()

Get the foreign type of the column.

The foreign type can be defined design time as a foreign key reference to another table.

Returns

[String](#) String foreign type.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var foreignType = column.getForeignType()
if (foreignType != null)
{
    var fkTable = databaseManager.getTable('example_data', foreignType)
}
```

getLength()

Get the length of the column as reported by the JDBC driver.

Returns

[Number](#) int column length.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customername')
if (column.getLength() < 10)
{
    // handle short column
}
```

getName()

Get the name of the column as used by Servoy.

Returns

[String](#) String column name

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var colName = column.getName()
```

getQualifiedName()

Get the qualified name (including table name) of the column as known by the database.
The name is quoted, if necessary, as defined by the actual database used.

Returns

[String](#) String qualified column name.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var qualifiedSqlName = column.getQualifiedName()
```

getQuotedSQLName()

Returns a quoted version of the column name, if necessary, as defined by the actual database used.

Returns

[String](#) column name, quoted if needed.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//use with the raw SQL plugin:
//if the table name contains characters that are illegal in sql, the table name will be quoted
var jsTable = databaseManager.getTable('udm', 'campaigns')
var quotedTableName = jsTable.getQuotedSQLName()
var jsColumn = jsTable.getColumn('active')
var quotedColumnName = jsColumn.getQuotedSQLName()
plugins.rawSQL.executeSQL('udm', quotedTableName, 'select * from ' + quotedTableName + ' where ' +
quotedColumnName + ' = ?', [1])
```

getRowIdentifierType()

Get the row identifier type of the column.
The sequence type is one of:

- JSColumn.PK_COLUMN
- JSColumn.ROWID_COLUMN
- JSColumn.NONE

Returns

[Number](#) int row identifier type.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getRowIdentifierType())
{
case JSColumn.NONE:
    // handle normal column
    break;

case JSColumn.PK_COLUMN:
    // handle database pk column
    break;

case JSColumn.ROWID_COLUMN:
    // handle developer defined pk column
    break;
}
```

getSQLName()

Get the name of the column as known by the database.

Returns

[String](#) String sql name

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var sqlName = column.getSQLName()
```

getSQLType()

Get the raw JDBC type of the column, which allows to check database specific types, like sting/byte column type variations.

Returns

[Number](#) int sql type.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var sqlType = column.getSQLType();
```

getScale()

Get the scale of the column as reported by the JDBC driver.

Returns

[Number](#) int column scale.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customername')
var scale = column.getScale()
```

getSequenceType()

Get the sequence type of the column.
The sequence type is one of:

- JSColumn.NONE
- JSColumn.SERVOY_SEQUENCE
- JSColumn.DATABASE_SEQUENCE
- JSColumn.DATABASE_IDENTITY
- JSColumn.UUID_GENERATOR;

Returns

[Number](#) int sequence type.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getSequenceType())
{
case JSColumn.NONE:
    // handle column with no sequence
    break;

case JSColumn.UUID_GENERATOR:
    // handle uuid generated column
    break;
}
```

getTable()

Get the JSTable of this column.

Returns

[JSTable](#) table The JSTable of this column.

Supported Clients

SmartClient,WebClient,NGClient

Sample**getTitle()**

Get the title property of the column. If title is null will return column name.

Returns

[String](#) String column title.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customername')
var title = column.getTitle()
```

getType()

Get the JDBC type of the column.
 The type reported by the JDBC driver will be mapped to one of:

- JSColumn.DATETIME
- JSColumn.TEXT
- JSColumn.NUMBER
- JSColumn.INTEGER
- JSColumn.MEDIA

Returns

[Number](#) int sql type.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
switch (column.getType())
{
case JSColumn.TEXT:
    // handle text column
    break;

case JSColumn.NUMBER:
case JSColumn.INTEGER:
    // handle numerical column
    break;
}
```

getTypeAsString()

Get the name JDBC type of the column.
 The same mapping as defined in JSColumn.getType() is applied.

Returns

[String](#) String sql name.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
var typeName = column.getTypeAsString()
```

hasFlag(flag)

Check a flag of the column.
 The flags are a bit pattern consisting of 1 or more of the following bits:

- JSColumn.UUID_COLUMN
- JSColumn.EXCLUDED_COLUMN
- JSColumn.TENANT_COLUMN
- JSColumn.NATIVE_COLUMN

Parameters

[Number](#) flag ;

Returns

[Boolean](#) boolean whether flag is set.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var table = databaseManager.getTable('db:/example_data/orders')
var column = table.getColumn('customerid')
if (column.hasFlag(JSColumn.UUID_COLUMN))
{
    // handle uuid column
}
```

