


Part

 Apr 05, 2024 18:14

Supported Clients

SmartClient WebClient NGClient

| Property Summary | | |
|------------------|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Boolean | allowBreakAcrossPageBounds | When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page. |
| String | background | The background color of the form part. |
| Boolean | discardRemainderAfterBreak | When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded. |
| String | groupbyDataProviderIDs | For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders. |
| Number | height | The height of a selected part; specified in pixels. |
| Number | pageBreakAfterOccurrence | A page break will be inserted after a specified number of occurrences of a selected part. |
| Boolean | pageBreakBefore | When set, a page break will be inserted before each occurrence of a selected part. |
| Number | partType | The type of this part. |
| Boolean | restartPageNumber | When set, page numbering will be restarted after each occurrence of a selected part. |
| Boolean | sinkWhenLast | When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space. |
| String | styleClass | The Cascading Style Sheet (CSS) class name applied to the part. |

Property Details

allowBreakAcrossPageBounds

When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.

NOTE: Make sure to set this option when you are printing more than one page per record.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient

Sample

background

The background color of the form part.

NOTE: When no background color has been set, the default background color will be determined by the Look and Feel (LAF) that has been selected in Application Preferences.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

discardRemainderAfterBreak

When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient

Sample**groupByDataProviderIDs**

For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders. The Leading/Trailing Subsummary parts will be displayed once for each resulted group of data.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**height**

The height of a selected part; specified in pixels.

This height property is the lowerbound as its ending Y value (0 == top of the form).

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**pageBreakAfterOccurrence**

A page break will be inserted after a specified number of occurrences of a selected part.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient

Sample**pageBreakBefore**

When set, a page break will be inserted before each occurrence of a selected part.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient

Sample**partType**

The type of this part.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**restartPageNumber**

When set, page numbering will be restarted after each occurrence of a selected part.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient

Sample

sinkWhenLast

When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient

Sample

styleClass

The Cascading Style Sheet (CSS) class name applied to the part.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample