

RuntimeForm

Property Summary

controller	#_super Provides access to the methods of the parent of this form.
Array	#alldataproviders Get all dataproviders of the form.
Array	#allmethods Get all script names of the form.
Array	#allnames Get the names of all elements on the form as an array.
Array	#allrelations Get all relation names of the form.
Array	#allvariables Get all form variable names.
controller	#controller Get the controller of the form.
elements	#elements Get an array with the elements in the form.
JSFoundset	#foundset Get the foundset of the form.

Property Details

[_super](#)
Provides access to the methods of the parent of this form.

Returns

[controller](#)

Sample

```
forms.customer._super.some_method();
```

[alldataproviders](#)
Get all dataproviders of the form.

Returns

[Array](#)

Sample

```
var dataprovidersNames = forms.customer.alldataproviders;
application.output("This form has " + dataprovidersNames.length + " data providers.")
for (var i=0; i<dataprovidersNames.length; i++)
    application.output(dataprovidersNames[i]);
```

[allmethods](#)
Get all script names of the form.

Returns

[Array](#)

Sample

```
var methodNames = forms.customer.allmethods;
application.output("This form has " + methodNames.length + " methods defined.")
for (var i=0; i<methodNames.length; i++)
    application.output(methodNames[i]);
```

[allnames](#)
Get the names of all elements on the form as an array.

Returns

[Array](#)

Sample

```
var names = forms.customer.allnames;
application.output("This form has " + names.length + " named items.")
for (var i=0; i<names.length; i++)
    application.output(names[i]);
```

allrelations

Get all relation names of the form.

Returns

[Array](#)

Sample

```
var relationsNames = forms.customer.allrelations;
application.output("This form has " + relationsNames.length + " relations.")
for (var i=0; i<relationsNames.length; i++)
    application.output(relationsNames[i]);
```

allvariables

Get all form variable names.

Returns

[Array](#)

Sample

```
var varNames = forms.customer.allvariables;
application.output("This form has " + varNames.length + " variables defined.")
for (var i=0; i<varNames.length; i++)
    application.output(varNames[i]);
```

controller

Get the controller of the form.

Returns

[controller](#)

Sample

```
forms.customer.controller.enabled = !forms.customer.controller.enabled;
```

elements

Get an array with the elements in the form.

Returns

[elements](#)

Sample

```
var elems = forms.customer.elements;
application.output("This form has " + elems.length + " named elements.")
for (var i=0; i<elems.length; i++)
    application.output(elems[i].getName());
```

foundset

Get the foundset of the form.

Returns

[JSFoundset](#)

Sample

```
application.output("selected index in form foundset: " + forms.customer.foundset.getSelectedIndex());
```