

JSRecord

Property Summary

[ServoyException](#) [#exception](#)
Returns last occurred exception on this record (or null).

[JSFoundset](#) [#foundset](#)
Returns parent foundset of the record.

Method Summary

[JSDataSet](#) [#getChangedData\(\)](#)
Returns a JSDataSet with outstanding (not saved) changed data of this record.

[String](#) [#getDataSource\(\)](#)
Returns the records datasource string.

[Object\[\]](#) [#getPKs\(\)](#)
Returns an array with the primary key values of the record.

[Boolean](#) [#isEditing\(\)](#)
Returns true or false if the record is being edited or not.

[void](#) [#rollbackChanges\(\)](#)
If this record exists in underlying datasource it will do a re-query to fetch the latest data from the datasource.

Property Details

[exception](#)
Returns last occurred exception on this record (or null).

Returns

[ServoyException](#) – The occurred exception.

Sample

```
var exception = record.exception;
```

[foundset](#)
Returns parent foundset of the record.

Returns

[JSFoundset](#) – The parent foundset of the record.

Sample

```
var parent = record.foundset;
```

Method Details

[getChangedData](#)
[JSDataSet](#) **getChangedData()**
Returns a JSDataSet with outstanding (not saved) changed data of this record.
column1 is the column name, column2 is the old data and column3 is the new data.

NOTE: To return an array of records with outstanding changed data, see the function [databaseManager.getEditedRecords\(\)](#).

Returns

[JSDataSet](#) – a JSDataSet with the changed data of this record.

Sample

```
var dataset = record.getChangedData()
for( var i = 1 ; i <= dataset.getMaxRowIndex() ; i++ )
{
    application.output(dataset.getValue(i,1) + ' ' + dataset.getValue(i,2) + ' ' + dataset.getValue(i,3));
}
```

[getDataSource](#)

`String` **getDataSource()**

Returns the records datasource string.

Returns

`String` – The datasource string of this record.

Sample

```
var ds = record.getDataSource();
```

`getPKs`

`Object[]` **getPKs()**

Returns an array with the primary key values of the record.

Returns

`Object[]` – an Array with the pk values.

Sample

```
var pks = foundset.getSelectedRecord().getPKs() // also foundset.getRecord can be used
```

`isEditing`

`Boolean` **isEditing()**

Returns true or false if the record is being edited or not.

Returns

`Boolean` – a boolean when in edit.

Sample

```
var isEditing = foundset.getSelectedRecord().isEditing() // also foundset.getRecord can be used
```

`rollbackChanges`

`void` **rollbackChanges()**

If this record exists in underlying datasource it will do a re-query to fetch the latest data from the datasource.

NOTE: If you use transactions then it will be the data of your last update of this record in the transaction, not the latest committed data of that record in the datasource.

Returns

`void`

Sample

```
var record= forms.customer.foundset.getSelectedRecord();
record.rollbackChanges();
```