DBDataSourceServer

Feb 28, 2024 22:13

Supported Clients

SmartClient WebClient NGClient

Methods Summary

JSConnectionDefinition	defineClientConnection()	Define a client connection for this server, you can configure this DB Server to create connections for this client that are configured by this JSConnection.
DBDataSourceServer	getDataModelCloneFrom()	Get the server where this server is a data model clone from.
String	getServerName()	Get the server name.
Array	getTableNames()	Returns an array with the names of all tables of this server.

Methods Details

defineClientConnection()

```
Define a client connection for this server, you can configure this DB Server to create connections for this
client that are configured by this JSConnection.
All interaction with the database will go over a connection coming from a specific client pool with that is
created for tihs client.
Things like username,password or connection properties can be adjusted.
```

Returns

JSConnectionDefinition DBDataSourceServer server

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var conncetionDefinition = datasources.db.example_data.defineClientConnection().setProperty('key', 'value').
create();
```

getDataModelCloneFrom()

```
Get the server where this server is a data model clone from.
```

Returns

DBDataSourceServer DBDataSourceServer server

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.db.example_data.getDataModelCloneFrom().getServerName()
```

getServerName()

```
Get the server name.
```

Returns

String String server name

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.db.example_data.getServerName() // returns 'example_data'
```

getTableNames()

```
Returns an array with the names of all tables of this server.
```

Returns

Array String[] server table names;

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.db.example_data.getTableNames()
```