

HeaderTitle

 Apr 03, 2024 16:16

Supported Clients

NGClient MobileClient

Property Summary

Number	anchors	Enables a component to stick to a specific side of form and/or to grow or shrink when a window is resized.
String	background	The background color of the component.
String	borderType	The type, color and style of border of the component.
String	comment	
CSSPosition	cssPosition	Thecss position of the component.
String	dataProvider	The dataprovider of the component.
Object	designTimeProperties	Property to get and add design-time properties for a component.
Boolean	displaysTags	Flag that enables or disables merging of data inside components using tags (placeholders).
Boolean	enabled	The enable state of the component, default true.
String	fontType	The font type of the component.
String	foreground	The foreground color of the component.
Number	formIndex	Form index returns the z-index of the form element.
String	format	The format that should be applied when displaying data(using dataProviderID) in the label /button.
Number	horizontalAlignment	Horizontal alignment of the text inside the component.
Number	imageMedia	The image Media object that should be displayed inside the component.
String	labelFor	Some components can be set to be labels of other components.
String	location	The x and y position of the component, in pixels, separated by a comma.
String	margin	The margins of the component.
Number	mediaOptions	Options to scale the image Media object that is displayed inside the component.
String	mnemonic	The keyboard shortcut that activates this component.
String	name	The name of the component.
Number	rolloverCursor	The cursor that is shown as the mouse is rolled over the component.
Number	rolloverImageMedia	The roll over image Media object used.
Boolean	showClick	When set, the element will show the clicked state when selected.
Boolean	showFocus	When set the text of an element will showfocus when selected.
String	size	The width and height (in pixels), separated by a comma.
String	styleClass	The name of the style class that should be applied to this component.
Number	tabSeq	An index that specifies the position of the component in the tab sequence.
String	text	The text that is displayed inside the component.
Number	textRotation	The rotation of the element.
String	toolTipText	The text displayed when hovering over the component with a mouse cursor.
Boolean	transparent	Flag that tells if the component is transparent or not.
Number	verticalAlignment	The vertical alignment of the text inside the component.
Boolean	visible	The visible property of the component, default true.

Event Summary

void	onAction()	
void	onDoubleClick(event)	The method that is executed when the component is double clicked.
void	onRightClick(event)	The method that is executed when the component is right clicked.

Property Details

anchors

Enables a component to stick to a specific side of form and/or to grow or shrink when a window is resized.

If opposite anchors are activated then the component with grow or shrink with the window. For example if Top and Bottom are activated, then the component will grow/shrink when the window is vertically resized. If Left and Right are activated then the component will grow/shrink when the window is horizontally resized.

If opposite anchors are not activated, then the component will keep a constant distance from the sides of the window which correspond to the activated anchors.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**background**

The background color of the component.

Returns[String](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**borderType**

The type, color and style of border of the component.

Returns[String](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**comment****Returns**[String](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**cssPosition**

Thecss position of the component.

Returns[CSSPosition](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample**dataProvider**

The dataprovider of the component.

Returns[String](#)**Supported Clients**

SmartClient,WebClient,NGClient,MobileClient

Sample**designTimeProperties**

Property to get and add design-time properties for a component.

Returns

[Object](#) map of the design-time properties

Supported Clients

SmartClient,WebClient,NGClient

Sample
displaysTags

Flag that enables or disables merging of data inside components using tags (placeholders). Tags (or placeholders) are words surrounded by %% on each side. There are data tags and standard tags. Data tags consist in names of dataproviders surrounded by %%. Standard tags are a set of predefined tags that are made available by the system.

See the "Merging data" section for more details about tags.

The default value of this flag is "false", that is merging of data is disabled by default.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample
enabled

The enable state of the component, default true.

Returns

[Boolean](#) enabled state

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample
fontType

The font type of the component.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
foreground

The foreground color of the component.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
formIndex

Form index returns the z-index of the form element. If two elements overlap, then the element with higher Z index is displayed above the form element with lower Z index. In case of form inheritance, form index is evaluated in the context (form) where property is defined. Elements which have child form as context will always be on top of elements which have parent form. If element is overridden in child form but form index property is still inherited its context is still parent form.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
format

The format that should be applied when displaying data(using dataProviderID) in the label/button. Some examples are "%#", "dd-MM-yyyy", "MM-dd-yyyy", etc.

Returns[String](#)**Supported Clients**

SmartClient,WebClient,NGClient,MobileClient

Sample
horizontalAlignment

Horizontal alignment of the text inside the component. Can be one of LEFT, CENTER or RIGHT.

Note that this property does not refer to the horizontal alignment of the component inside the form.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
imageMedia

The image Media object that should be displayed inside the component.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
labelFor

Some components can be set to be labels of other components. This is useful in two situations. In table view mode it is used for constructing the header of the table. In record view mode, by setting mnemonics on the label, keyboard shortcuts can be used to set the focus to fields.

Returns[String](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
location

The x and y position of the component, in pixels, separated by a comma.

Returns[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample**margin**

The margins of the component. They are specified in this order, separated by commas: top, left, bottom, right.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**mediaOptions**

Options to scale the image Media object that is displayed inside the component. Can be set to one or a combination of CROP, REDUCE, ENLARGE and KEEPASPECT.

REDUCE will scale down the image if the component is smaller than the image. REDUCE combined with KEEPASPECT will reduce the image, but keep its aspect ratio. This is useful when the component has other proportions than the image.

ENLARGE will scale up the image if the component is larger than the image. ENLARGE combined with KEEPASPECT will scale up the image while keeping its aspect ratio.

CROP will leave the image at its original size. If the component is smaller than the image this will result in only a part of the image showing up.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**mnemonic**

The keyboard shortcut that activates this component. A letter must be specified, and the actual shortcut will be combination of ALT + the specified letter.

This property can be used in two ways. Normally the keyboard shortcut activates the onClick event of the component. But if the "labelFor" property is set for the component, then the keyboard shortcut will move the focus to the component whose label this component is.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample**name**

The name of the component. Through this name it can also accessed in methods. Must be a valid javascript name. (no - in the name or start with number)

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample**rolloverCursor**

The cursor that is shown as the mouse is rolled over the component. Possible options are DEFAULT and HAND. Note that roll over cursor is not supported in Smart client for list view and tableview forms.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
rolloverImageMedia

The roll over image Media object used. It will only work if a property image is also used. When the mouse is moved over the component, this image Media will be displayed. When the mouse is moved out of the component, whatever text or image was being initially displayed will be restored. Note that roll over image is not supported in Smart client for list view and tableview forms.

Returns[Number](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
showClick

When set, the element will show the clicked state when selected. Applies to labels and buttons and images only.

Returns[Boolean](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
showFocus

When set the text of an element will showfocus when selected. Applies to labels and buttons only. The text property for the element MUST be filled in first.

NOTE: The TAB key may also be used to select the element, depending on the operating system being used and the selected LAF.

Returns[Boolean](#)**Supported Clients**

SmartClient,WebClient,NGClient

Sample
size

The width and height (in pixels), separated by a comma.

Returns[String](#)**Supported Clients**

NGClient

Sample
styleClass

The name of the style class that should be applied to this component.

When defining style classes for specific component types, their names must be prefixed according to the type of the component. For example in order to define a class names 'fancy' for fields, in the style definition the class must be named 'field.fancy'. If it would be intended for labels, then it would be named 'label.fancy'. When specifying the class name for a component, the prefix is dropped however. Thus the field or the label will have its styleClass property set to 'fancy' only.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
tabSeq

An index that specifies the position of the component in the tab sequence. The components are put into the tab sequence in increasing order of this property. A value of 0 means to use the default mechanism of building the tab sequence (based on their location on the form). A value of -2 means to remove the component from the tab sequence.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
text

The text that is displayed inside the component.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample
textRotation

The rotation of the element. You can choose 0, 90, 180, or 270 and the label is rotated accordingly. This property also applies to buttons and images.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample
toolTipText

The text displayed when hovering over the component with a mouse cursor.

NOTE:

HTML should be used for multi-line tooltips; you can also use any valid HTML tags to format tooltip text. For example:
<html>This includesbolded text and
BLUE text as well.</html>

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample



transparent

Flag that tells if the component is transparent or not.

The default value is "false", that is the components are not transparent.


Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample



verticalAlignment

The vertical alignment of the text inside the component. Can be one of TOP, CENTER or BOTTOM.

Note that this property does not refer to the vertical alignment of the component inside the form.


Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample



visible

The visible property of the component, default true.


Returns

[Boolean](#) visible property

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample




Event Details

onAction()

Supported Clients

SmartClient,WebClient,NGClient

Sample



onDoubleClick(event)

The method that is executed when the component is double clicked.


Parameters

[JSEvent](#) event the event that triggered the action

Supported Clients

SmartClient,WebClient,NGClient

Sample



onRightClick(event)

The method that is executed when the component is right clicked.

Parameters

[JSEvent](#) event the event that triggered the action

Supported Clients

SmartClient,WebClient,NGClient

Sample