

Datasources

 Apr 07, 2024 13:11

Return Types

[DBDataSource](#) [MemDataSource](#) [JSDataSource](#) [JSConnectionDefinition](#) [DBDataSourceServer](#) [ViewDataSource](#)

Supported Clients

SmartClient WebClient NGClient

Property Summary	
DBDataSource <code>db</code>	Scope property for server/table based data sources.
MemDataSource <code>mem</code>	Scope property for in-memory data sources.
SPDataSource <code>sp</code>	Scope property for stored procedures.
ViewDataSource <code>view</code>	Scope property for view foundset data sources.

Property Details

db
Scope property for server/table based data sources.

Returns

[DBDataSource](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.db.example_data.orders
```

mem
Scope property for in-memory data sources.

Returns

[MemDataSource](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.mem['mysds']
```

sp
Scope property for stored procedures.
This will list the stored procedures of server that have this property enabled (see server editor).

Returns

[SPDataSource](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
datasources.sp.servername.mystoredproc();
```

view
Scope property for view foundset data sources.

Returns

[ViewDataSource](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
datasources.view[ 'mysds' ]
```