

RuntimeComponent



Apr 07, 2024 13:19

Supported Clients

SmartClient WebClient NGClient

Extends

Component

Property Summary

| | | |
|---------|-------------|--|
| String | bgcolor | Gets or sets the background color of a field. |
| String | border | Gets or sets the border attribute(s) of a specified element. |
| Boolean | enabled | Gets or sets the enabled state of a specified field, also known as "grayed". |
| String | fgcolor | Gets or sets the foreground color of a field. |
| String | font | Gets or sets the font name, style, and size of an element. |
| String | toolTipText | Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element. |
| Boolean | transparent | Gets or sets the transparency of an element; true - transparent; false - not transparent. |
| Boolean | visible | Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite). |

Methods Summary

| | | |
|--------|-------------------------------|--|
| void | addStyleClass(styleName) | Adds a style to the styleClass property. |
| Number | getAbsoluteFormLocationY() | Returns the absolute form (designed) Y location. |
| Object | getClientProperty(key) | Gets the specified client property for the element based on a key. |
| Object | getDesignProperties() | Get the design-time properties of an element. |
| Object | getDesignTimeProperty(key) | Get a design-time property of an element. |
| String | getElementType() | Returns the type of a specified element. |
| String | getFormName() | Returns the name of the form. |
| Number | getHeight() | Returns the height of the current element. |
| Number | getLocationX() | Returns the x location of the current element. |
| Number | getLocationY() | Returns the y location of the current element. |
| String | getName() | Returns the name of an element. |
| Number | getWidth() | Returns the width of the current element. |
| void | hasStyleClass(styleName) | Check if an element already have a style from the styleClass property. |
| void | putClientProperty(key, value) | Sets the value for the specified element client property key. |
| void | removeStyleClass(styleName) | Removes a style from the styleClass property. |
| void | setLocation(x, y) | Sets the location of an element. |
| void | setSize(width, height) | Sets the size of an element. |

Property Details

bgcolor

Gets or sets the background color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.
It only returns it's correct value if it was explicitly set.

Returns

String

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//sets the background color of the field
%%elementName%.bgcolor = "#FFFFFF";
//gets the background color of the field
var c = %%elementName%.bgcolor;
```

border

Gets or sets the border attribute(s) of a specified element.

The border attributes:

borderType - EmptyBorder, EtchedBorder, BevelBorder, LineBorder, TitleBorder, MatteBorder, SpecialMatteBorder.
 size - (numeric value) for: bottom, left, right, top.
 color - (hexadecimal value) for: bottom, left, right, top.
 dash pattern - (numeric value) for selected side(s).
 rounding radius - (numeric value) for selected side(s).

It only returns it's correct value if it was explicitly set.

NOTE: Use the same value(s) and order of attribute(s) from the element design time property "borderType".

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//sets the border type to "LineBorder"
//sets a 1 px line width for the bottom and left side of the border
//sets the hexadecimal color of the border to "#ccffcc"
%%elementName%%.border = 'LineBorder,1,#ccffcc';
```

enabled

Gets or sets the enabled state of a specified field, also known as "grayed".
 true - enabled; false - not enabled; ! - the enabled state is inverted (the opposite).

NOTE: A disabled element cannot be selected by clicking the element (or by pressing the TAB key even if this option is supported by the operating system).

NOTE: A label or button element will not disable if the "displayType" design time property for a field is set to HTML_AREA.

NOTE: The disabled "grayed" color is dependent on the LAF set in the Servoy Client Application Preferences. For more information see Preferences: Look And Feel in the Servoy Developer User's Guide.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//gets the enabled state of the field
var currState = %%elementName%%.enabled;

//sets the enabled state of the field
%%elementName%%.enabled = !currentState;
```

fgcolor

Gets or sets the foreground color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.

It only returns it's correct value if it was explicitly set.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//sets the foreground color of the field
%%elementName%%.fgcolor = "#000000";

//gets the foreground color of the field
var c = %%elementName%%.fgcolor;
```

font

Gets or sets the font name, style, and size of an element.

font name - the name of the font family.
 style - the type of the font. (plain = 0; bold = 1; italic = 2; bold-italic = 3).
 size - the size of the font (in points).

It only returns it's correct value if it was explicitly set.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
%%elementName%%.font = 'Tahoma,1,11';
```

toolTipText

Gets or sets the tool tip text of an element; text displays when the mouse cursor hovers over an element.

NOTE: HTML should be used for multi-line tooltips; you can also use any valid HTML tags to format tooltip text.

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//gets the tooltip text of the element
var toolTip = %%elementName%%.toolTipText;

//sets the tooltip text of the element
%%elementName%%.toolTipText = "New tip";
%%elementName%%.toolTipText = "<html>This includes <b>bolded text</b> and <font color='blue'>BLUE</font> text as well.";
```

transparent

Gets or sets the transparency of an element; true - transparent; false - not transparent.

NOTE: transparency can be inverted using ! operator: elements.elementName.transparent = !elements.elementName.transparent;

NOTE: transparency will be mostly used for background color, a transparent element will receive the background of the element "beneath" it, a non transparent one will use its own background color

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//gets the transparency of the element
var currentState = %%elementName%%.transparent;

//sets the transparency of the element
%%elementName%%.transparent = !currentState;
```

visible

Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

NOTE: The visibility of an element is not persistent; the state of visibility only applies to the current user in his/her current session.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//sets the element as visible
forms.company.elements.faxBtn.visible = true;

//gets the visibility of the element
var currentState = forms.company.elements.faxBtn.visible;

//sets the element as not visible when the current state is visible
forms.company.elements.faxBtn.visible = !currentState;
```

Methods Details**addStyleClass(styleName)**

Adds a style to the styleClass property. This works only for NGClient where multiple styles are supported.

Parameters

[String](#) styleName the name of the style class to add

Supported Clients

NGClient

Sample

```
%%elementName%%.addStyleClass('redbg');
```

getAbsoluteFormLocationY()

Returns the absolute form (designed) Y location.

Returns

[Number](#) The y location of the form in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var absolute_y = %%elementName%%.getAbsoluteFormLocationY();
```

getClientProperty(key)

Gets the specified client property for the element based on a key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

[Object](#) key user interface key (depends on operating system)

Returns

[Object](#) The value of the property for specified key.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var property = %%elementName%%.getClientProperty('ToolTipText');
```

getDesignProperties()

Get the design-time properties of an element.

Returns

[Object](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var prop = forms.orders.elements.mylabel.getDesignProperties()
```

getDesignTimeProperty(key)

Get a design-time property of an element.

Parameters

[String](#) key the name of the property

Returns

[Object](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var prop = forms.orders.elements.mylabel.getDesignTimeProperty('myprop')
```

getElementType()

Returns the type of a specified element.

Returns

[String](#) The display type of the element as String.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var et = %%elementName%%.getElementType();
```

getFormName()

Returns the name of the form. (may be empty string as well)

Returns

[String](#) The name of the form.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var name = %%elementName%%.getFormName();
```

getHeight()

Returns the height of the current element.

NOTE: getHeight() can be used with getWidth() to set the size of an element using the setSize function. For example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

[Number](#) The height of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var ht = %%elementName%%.getHeight();
```

getLocationX()

Returns the x location of the current element.

NOTE: getLocationX() can be used with getLocationY() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

[Number](#) The x location of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var x = %%elementName%%.getLocationX();
```

getLocationY()

Returns the y location of the current element. The method can only be used in Record view.

NOTE: getLocationY() can be used with getLocationX() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

[Number](#) The y location of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var y = %%elementName%%.getLocationY();
```

getName()

Returns the name of an element. (may be null as well)

Returns

[String](#) The name of the element.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var name = %%elementName%%.getName();
```

getWidth()

Returns the width of the current element.

NOTE: `getWidth()` can be used with `getHeight()` to set the size of an element using the `setSize` function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

[Number](#) The width of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var w = %%elementName%%.getWidth();
```

hasStyleClass(styleName)

Check if an element already have a style from the `styleClass` property.

Parameters

[String](#) `styleName` the name of the style class to be checked

Supported Clients

NGClient

Sample

```
%%elementName%%.hasStyleClass('redbg');
```

putClientProperty(key, value)

Sets the value for the specified element client property key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

[Object](#) `key` user interface key (depends on operating system)

[Object](#) `value` a predefined value for the key

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
%%elementName%%.putClientProperty('ToolTipText','some text');
```

removeStyleClass(styleName)

Removes a style from the `styleClass` property. This works only for NGClient where multiple styles are supported.

Parameters

[String](#) `styleName` the name of the style class to remove

Supported Clients

NGClient

Sample

```
%%elementName%%.removeStyleClass('redbg');
```

setLocation(x, y)

Sets the location of an element. It takes as input the X (horizontal) and Y (vertical) coordinates - starting from the TOP LEFT side of the screen.
Please note that location should not be altered at runtime when an element is anchored. Use the solutionModel in such a situation.

NOTE: getLocationX() can be used with getLocationY() to return the current location of an element; then use the X and Y coordinates with the setLocation function to set a new location. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Parameters

[Number](#) x the X coordinate of the element in pixels.

[Number](#) y the Y coordinate of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
%%elementName%%.setLocation(200,200);
```

setSize(width, height)

Sets the size of an element. It takes as input the width and the height.
Please note that size should not be altered at runtime when an element is anchored. Use the solutionModel in such a situation.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();

//sets the new size
forms.company.elements.faxBtn.setSize(w,h);

//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Parameters

[Number](#) width the width of the element in pixels.

[Number](#) height the height of the element in pixels.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
%%elementName%%.setSize(20,30);
```