

RuntimePortal

Property Summary

String	#bgcolor	Gets or sets the background color of a field.
String	#border	Gets or sets the border attribute(s) of a specified element.
Boolean	#enabled	Gets or sets the enabled state of a specified field, also known as "grayed".
String	#fgcolor	Gets or sets the foreground color of a field.
Boolean	#readOnly	Gets or sets the editable/read-only state of a field; true - read-only; false - editable; ! - the editable/read-only state is inverted (the opposite).
Boolean	#visible	Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

Method Summary

void	#deleteRecord()	Deletes the currently selected portal row in the foundset of the specified portal.
void	#duplicateRecord([addOnTop])	Duplicates the currently selected portal row in the foundset of the specified portal.
Number	#getAbsoluteFormLocationY()	Returns the absolute form (designed) Y location.
Object	#getClientProperty(key)	Gets the specified client property for the element based on a key.
String	#getElementType()	Returns the type of a specified element.
Number	#getHeight()	Returns the height of the current element.
Number	#getLocationX()	Returns the x location of the current element.
Number	#getLocationY()	Returns the y location of the current element.
String	#getName()	Returns the name of an element.
Number	#getScrollX()	Returns the x scroll location of the current portal or specified portal - only for a portal where the height of the portal is greater than the height of the portal field(s).
Number	#getScrollY()	Returns the y scroll location of the current portal or specified portal - only for a portal where the height of the portal is greater than the height of the portal field(s).
Number	#getSelectedIndex()	Gets the selected record index in the current cached foundset in the specified portal.
String	#getSortColumns()	Returns the sort columns names of the current portal (as comma separated string).
Number	#getWidth()	Returns the width of the current element.
void	#newRecord([addOnTop])	Creates a new portal row in the foundset of the specified portal.
void	#putClientProperty(key, value)	Sets the value for the specified element client property key.
void	#setLocation(x, y)	Sets the location of an element.
void	#setScroll(x, y)	Sets the scroll location of a portal.
void	#setSelectedIndex(index)	Sets the selected record index in the current cached foundset in the specified portal.
void	#setSize(width, height)	Sets the size of the field.

Property Details

bgcolor

Gets or sets the background color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.

Returns

String

Sample

```
//sets the background color of the field
forms.customer.elements.customer_id bgcolor = "#FFFFFF";
//gets the background color of the field
var c = forms.customer.elements.customer_id bgcolor;
```

border

Gets or sets the border attribute(s) of a specified element.

The border attributes:

borderType - EmptyBorder, EtchedBorder, BevelBorder, LineBorder, TitleBorder, MatteBorder, SpecialMatteBorder.

size - (numeric value) for: bottom, left, right, top.

color - (hexadecimal value) for: bottom, left, right, top.

dash pattern - (numeric value) for selected side(s).

rounding radius - (numeric value) for selected side(s).

NOTE: Use the same value(s) and order of attribute(s) from the element design time property "borderType".

Parameters

spec – the border attributes

Returns

String

Sample

```
//sets the border type to "LineBorder"
//sets a 1 px line width for the bottom and left side of the border
//sets the hexadecimal color of the border to "#ccffcc"
var b = forms.customer.elements.customer_id.setBorder('LineBorder,1,#ccffcc');
```

enabled

Gets or sets the enabled state of a specified field, also known as "grayed".

true - enabled; false - not enabled; ! - the enabled state is inverted (the opposite).

NOTE: A disabled element cannot be selected by clicking the element (or by pressing the TAB key even if this option is supported by the operating system).

NOTE: A label or button element will not disable if the "displayType" design time property for a field is set to HTML_AREA.

NOTE: The disabled "grayed" color is dependent on the LAF set in the Servoy Client Application Preferences. For more information see Preferences: Look And Feel in the Servoy Developer User's Guide.

Returns

Boolean

Sample

```
//gets the enabled state of the field
var currState = forms.customer.elements.customer_id.enabled;

//sets the enabled state of the field
forms.customer.elements.customer_id.enabled = !currentState;
```

fgcolor

Gets or sets the foreground color of a field. The color has to be set using the hexadecimal RGB value as used in HTML.

Returns

String

Sample

```
//sets the foreground color of the field
forms.customer.elements.customer_id.fgcolor = "#000000";

//gets the foreground color of the field
var c = forms.customer.elements.customer_id.fgcolor;
```

readOnly

Gets or sets the editable/read-only state of a field; true - read-only; false - editable; ! - the editable/read-only state is inverted (the opposite).

NOTE: A field set as read-only can be selected by clicking (or pressing the TAB key if this option is supported by the operating system) and the field data can be copied.

Returns

Boolean

Sample

```
//gets the editable/read-only state of the field
var currentState = forms.customer.elements.customer_id.readOnly;

//sets the editable/read-only state of the field
forms.customer.elements.customer_id.readOnly = !currentState;
```

visible

Gets or sets the visibility of an element; true - visible; false - not visible; ! - the visibility state is inverted (the opposite).

NOTE: The visibility of an element is not persistent; the state of visibility only applies to the current user in his/her current session.

Returns

Boolean

Sample

```
//sets the element as visible
forms.company.elements.faxBtn.visible = true;

//gets the visibility of the element
var currentState = forms.company.elements.faxBtn.visible;

//sets the element as not visible when the current state is visible
forms.company.elements.faxBtn.visible = !currentState;
```

Method Details

deleteRecord

void **deleteRecord()**

Deletes the currently selected portal row in the foundset of the specified portal.

Returns

void

Sample

```
forms.customer.elements.customer_id.deleteRecord();
```

duplicateRecord

void **duplicateRecord**([addOnTop])

Duplicates the currently selected portal row in the foundset of the specified portal.

Parameters

[addOnTop] – adds the duplicated record as the topmost record of the foundset, default value is true

Returns

void

Sample

```
//adds the duplicated record on top
forms.customer.elements.customer_id.duplicateRecord(true);
```

getAbsoluteFormLocationY

Number **getAbsoluteFormLocationY()**

Returns the absolute form (designed) Y location.

Returns

Number – The y location of the form in pixels.

Sample

```
var absolute_y = forms.customer.elements.customer_id.getAbsoluteFormLocationY();
```

getClientProperty

Object **getClientProperty(key)**

Gets the specified client property for the element based on a key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

{Object} key – user interface key (depends on operating system)

Returns

Object – The value of the property for specified key.

Sample

```
var property = forms.customer.elements.customer_id.getClientProperty('ToolTipText');
```

getElementType

String **getElementType()**

Returns the type of a specified element.

Returns

String – The display type of the element as String.

Sample

```
var et = forms.customer.elements.customer_id.getElementType();
```

getHeight

Number **getHeight()**

Returns the height of the current element.

NOTE: getHeight() can be used with getWidth() to set the size of an element using the setSize function. For example:

```
//returns the width (w) and height (h)
```

```
var w = forms.company.elements.faxBtn.getWidth();
```

```
var h = forms.company.elements.faxBtn.getHeight();
```

```
//sets the new size
```

```
forms.company.elements.faxBtn.setSize(w,h);
```

```
//sets the new size and adds 1 px to both the width and height
```

```
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

Number – The height of the element in pixels.

Sample

```
var ht = forms.customer.elements.customer_id.getHeight();
```

getLocationX

Number **getLocationX()**

Returns the x location of the current element.

NOTE: getLocationX() can be used with getLocationY() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number – The x location of the element in pixels.

Sample

```
var x = forms.customer.elements.customer_id.getLocationX();
```

getLocationY

Number **getLocationY()**

Returns the y location of the current element.

NOTE: getLocationY() can be used with getLocationX() to set the location of an element using the setLocation function. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();

//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Returns

Number – The y location of the element in pixels.

Sample

```
var y = forms.customer.elements.customer_id.getLocationY();
```

getName

String **getName()**

Returns the name of an element. (may be null as well)

Returns

String – The name of the element.

Sample

```
var name = forms.customer.elements.customer_id.getName();
```

getScrollX

Number **getScrollX()**

Returns the x scroll location of the current portal or specified portal - only for a portal where the height of the portal is greater than the height of the portal field(s).

NOTE: getScrollX() can be used with getScrollY() to set the scroll location of a portal using the setScroll function. For Example:

```
//returns the X and Y scroll coordinates
var x = forms.company.elements.portal50.getScrollX();
var y = forms.company.elements.portal50.getScrollY();

//sets the new scroll location
forms.company.elements.portal50.setScroll(x+10,y+10);
```

Returns

Number – The x scroll location in pixels.

Sample

```
var x = forms.customer.elements.customer_id.getScrollX();
```

getScrollY

Number **getScrollY()**

Returns the y scroll location of the current portal or specified portal - only for a portal where the height of the portal is greater than the height of the portal field(s).

NOTE: `getScrollY()` can be used with `getScrollX()` to set the scroll location of a portal using the `setScroll` function. For Example:

```
//returns the X and Y scroll coordinates
var x = forms.company.elements.portal50.getScrollX();
var y = forms.company.elements.portal50.getScrollY();
```

```
//sets the new scroll location
forms.company.elements.portal50.setScroll(x+10,y+10);
```

Returns

Number – The y scroll location in pixels.

Sample

```
var y = forms.customer.elements.customer_id.getScrollY();
```

getSelectedIndex

Number **getSelectedIndex()**

Gets the selected record index in the current cached foundset in the specified portal.

Returns

Number – The selected index (integer).

Sample

```
//gets the selected record index in the foundset
var current = forms.customer.elements.customer_id.getSelectedIndex();

//sets the next record index in the foundset
forms.customer.elements.customer_id.setSelectedIndex(current+1);
```

getSortColumns

String **getSortColumns()**

Returns the sort columns names of the current portal (as comma separated string).

Returns

String – array with column names

Sample

```
var w = forms.customer.elements.customer_id.getSortColumns();
```

getWidth

Number **getWidth()**

Returns the width of the current element.

NOTE: `getWidth()` can be used with `getHeight()` to set the size of an element using the `setSize` function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();
```

```
//sets the new size
forms.company.elements.faxBtn.setSize(w,h);
```

```
//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Returns

Number – The width of the element in pixels.

Sample

```
var w = forms.customer.elements.customer_id.getWidth();
```

newRecord

void **newRecord**([addOnTop])

Creates a new portal row in the foundset of the specified portal.

Parameters

[addOnTop] – adds the new portal record as the topmost row of the foundset, default value is true

Returns

void

Sample

```
// foreign key data is only filled in for equals (=) relation items
//adds the new record on top
forms.customer.elements.customer_id.newRecord(true);
```

putClientProperty

void **putClientProperty**(key, value)

Sets the value for the specified element client property key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

{Object} key – user interface key (depends on operating system)

{Object} value – a predefined value for the key

Returns

void

Sample

```
forms.customer.elements.customer_id.putClientProperty('ToolTipText', 'some text');
```

setLocation

void **setLocation**(x, y)

Sets the location of an element. It takes as input the X (horizontal) and Y (vertical) coordinates - starting from the TOP LEFT side of the screen.

NOTE: getLocationX() can be used with getLocationY() to return the current location of an element; then use the X and Y coordinates with the setLocation function to set a new location. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.faxBtn.getLocationX();
var y = forms.company.elements.faxBtn.getLocationY();
```

```
//sets the new location 10 px to the right; 10 px down from the current location
forms.company.elements.faxBtn.setLocation(x+10,y+10);
```

Parameters

{Number} x – the X coordinate of the element in pixels.

{Number} y – the Y coordinate of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setLocation(200,200);
```

setScroll

void **setScroll**(x, y)

Sets the scroll location of a portal. It takes as input the X (horizontal) and Y (vertical) coordinates - starting from the TOP LEFT side of the screen - only for a portal where the height of the portal is greater than the height of the portal filed(s).

NOTE: getScrollX() can be used with getScrollY() to return the current scroll location of a portal; then use the X and Y coordinates with the setScroll function to set a new scroll location. For Example:

```
//returns the X and Y coordinates
var x = forms.company.elements.portal50.getScrollX();
var y = forms.company.elements.portal50.getScrollY();
```

```
//sets the new location
forms.company.elements.portal50.setScroll(x+10,y+10);
```

Parameters

{Number} x – the X coordinate of the portal scroll location in pixels

{Number} y – the Y coordinate of the portal scroll location in pixels

Returns

void

Sample

```
forms.customer.elements.customer_id.setScroll(200,200);
```

setSelectedIndex

void **setSelectedIndex**(index)

Sets the selected record index in the current cached foundset in the specified portal.

Parameters

{[Number](#)} index – the specified record index

Returns

void

Sample

```
//gets the selected record index in the foundset
var current = forms.customer.elements.customer_id.getSelectedIndex();

//sets the next record index in the foundset
forms.customer.elements.customer_id.setSelectedIndex(current+1);
```

setSize

void **setSize**(width, height)

Sets the size of the field. It takes as input the width and the height.

NOTE: getWidth() can be used with getHeight() to set the size of an element using the setSize function. For Example:

```
//returns the width (w) and height (h)
var w = forms.company.elements.faxBtn.getWidth();
var h = forms.company.elements.faxBtn.getHeight();
```

```
//sets the new size
forms.company.elements.faxBtn.setSize(w,h);
```

```
//sets the new size and adds 1 px to both the width and height
forms.company.elements.faxBtn.setSize(w+1,h+1);
```

Parameters

{[Number](#)} width – the width of the element in pixels.

{[Number](#)} height – the height of the element in pixels.

Returns

void

Sample

```
forms.customer.elements.customer_id.setSize(20,30);
```