

Mail Server

Server Property Summary

[#mail.development.override.address](#)
[#mail.from](#)
[#mail.mime.charset](#)
[#mail.pop3.apop.enable](#)
[#mail.pop3.host](#)
[#mail.server.allowUnauthenticatedRMIAccess](#)
[#mail.smtp.auth](#)
[#mail.smtp.connectiontimeout](#)
[#mail.smtp.host](#)
[#mail.smtp.password](#)
[#mail.smtp.port](#)
[#mail.smtp.ssl.enable](#)
[#mail.smtp.timeout](#)
[#mail.smtp.username](#)

Server Property Details

[mail.development.override.address](#)

Specify an email address to which all email will be send instead of the specified To, Cc and Bcc addresses. The specified to, Cc and Bcc addresses will be added to the Subject.

[mail.from](#)

Default 'from' address if none is specified

[mail.mime.charset](#)

Specify the name of the charset to use for mail encoding (leave empty for system default), see <http://java.sun.com/j2se/1.4.2/docs/api/java/nio/charset/Charset.html> for info which charset names are usable

[mail.pop3.apop.enable](#)

Whether or not to use APOP for authentication (true/false), defaults to false.

[mail.pop3.host](#)

The name of POP3 server to receive mails from

[mail.server.allowUnauthenticatedRMIAccess](#)

Allow mailserver access for unauthenticated smart (rmi) client (true/false), defaults to false

[mail.smtp.auth](#)

Use authentication (true/false), defaults to false.

[mail.smtp.connectiontimeout](#)

Socket connection timeout value in milliseconds. Default is infinite timeout.

[mail.smtp.host](#)

The name of SMTP server to deliver the mails to

[mail.smtp.password](#)

Specify password if using authentication

[mail.smtp.port](#)

The port of SMTP server to deliver the mails to

[mail.smtp.ssl.enable](#)

Use SSL (true/false), defaults to false .

[mail.smtp.timeout](#)

Socket I/O timeout value in milliseconds. Default is infinite timeout.

[mail.smtp.username](#)

Specify username if using authentication