dialogs

Feb 26, 2024 08:57

Supported Clients

SmartClient WebClient NGClient MobileClient

Methods Summary

String	showErrorDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showInfoDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showInputDialog()	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title)	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title, msg)	Shows an input dialog where the user can enter data.
String	showInputDialog(dialog_title, msg, initialValue)	Shows an input dialog where the user can enter data.
String	showQuestionDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.
String	showSelectDialog(dialog_title, msg, optionArray)	Shows a selection dialog, where the user can select an entry from a list of options.
String	showSelectDialog(dialog_title, msg, options)	Shows a selection dialog, where the user can select an entry from a list of options.
String	showWarningDialog(dialogTitle, dialogMessage, buttonsText)	Shows a message dialog with the specified title, message and a customizable set of buttons.

Methods Details

showErrorDialog(dialogTitle, dialogMessage, buttonsText)

```
Shows a message dialog with the specified title, message and a customizable set of buttons.
Returns pressed button text, in case window is closed without pressing any button return value depends on
client type.
```

Parameters

String	dialogTitle	Dialog title.
String	dialogMessage	Dialog message.
Array	buttonsText	Array of button texts.

Returns

String pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showErrorDialog('Title', 'Value not allowed','OK');
```

showInfoDialog(dialogTitle, dialogMessage, buttonsText)

```
Shows a message dialog with the specified title, message and a customizable set of buttons.
Returns pressed button text, in case window is closed without pressing any button return value depends on
client type.
```

Parameters

String	dialogTitle	Dialog title.
String	dialogMessage	Dialog message.
Array	buttonsText	Array of button texts.

Returns

String pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showInfoDialog('Title', 'Value not allowed','OK');
```

showInputDialog()

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Returns

String input text or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

String dialog_title ;

Returns

String input text or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title, msg)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

String dialog_title ;
String msg ;

Returns

String input text or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showInputDialog(dialog_title, msg, initialValue)

Shows an input dialog where the user can enter data. Returns the entered data, or nothing when canceled.

Parameters

String dialog_title ;
String msg ;
String initialValue ;

Returns

String input text or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show input dialog ,returns nothing when canceled
var typedInput = plugins.dialogs.showInputDialog('Specify','Your name');
```

showQuestionDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons. Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

String	dialogTitle	Dialog title.
String	dialogMessage	Dialog message.
Array	buttonsText	Array of button texts.

Returns

String pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showQuestionDialog('Title', 'Value not allowed','OK');
```

showSelectDialog(dialog_title, msg, optionArray)

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

Parameters

String	dialog_title	;
String	msg	;
Array	optionArray	;

Returns

String selected value or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show select,returns nothing when canceled
var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name','jan','johan','sebastiaan');
//also possible to pass array with options
//var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name', new Array
('jan','johan','sebastiaan'));
```

showSelectDialog(dialog_title, msg, options)

Shows a selection dialog, where the user can select an entry from a list of options. Returns the selected entry, or nothing when canceled.

Parameters

String	dialog_title	;
String	msg	;
Array	options	;

Returns

String selected value or null

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show select,returns nothing when canceled
var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name','jan','johan','sebastiaan');
//also possible to pass array with options
//var selectedValue = plugins.dialogs.showSelectDialog('Select','please select a name', new Array
('jan','johan','sebastiaan'));
```

showWarningDialog(dialogTitle, dialogMessage, buttonsText)

Shows a message dialog with the specified title, message and a customizable set of buttons. Returns pressed button text, in case window is closed without pressing any button return value depends on client type.

Parameters

String	dialogTitle	Dialog title.
String	dialogMessage	Dialog message.
Array	buttonsText	Array of button texts.

Returns

String pressed button text

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
//show dialog
var thePressedButton = plugins.dialogs.showWarningDialog('Title', 'Value not allowed','OK');
```