

Mail Server

Server Property Summary

#mail.development.override.address
#mail.from
#mail.mime.charset
#mail.pop3.apop.enable
#mail.pop3.host
#mail.server.allowUnauthenticatedRMIAccess
#mail.smtp.auth
#mail.smtp.connectiontimeout
#mail.smtp.host
#mail.smtp.password
#mail.smtp.port
#mail.smtp.ssl.enable
#mail.smtp.timeout
#mail.smtp.username

Server Property Details

mail.development.override.address

Specify an email address to which all email will be send instead of the specified To, Cc and Bcc addresses. The specified to, Cc and Bcc addresses will be added to the Subject.

mail.from

Default 'from' address if none is specified

mail.mime.charset

Specify the name of the charset to use for mail encoding (leave empty for system default), see <http://java.sun.com/j2se/1.4.2/docs/api/java/nio/charset/Charset.html> for info which charset names are usable

mail.pop3.apop.enable

Whether or not to use APOP for authentication (true/false), defaults to false.

mail.pop3.host

The name of POP3 server to receive mails from

mail.server.allowUnauthenticatedRMIAccess

Allow mailserver access for unauthenticated smart (rmi) client (true/false), defaults to false

mail.smtp.auth

Use authentication (true/false), defaults to false.

mail.smtp.connectiontimeout

Socket connection timeout value in milliseconds. Default is infinite timeout.

mail.smtp.host

The name of SMTP server to deliver the mails to

mail.smtp.password

Specify password if using authentication

mail.smtp.port

The port of SMTP server to deliver the mails to

mail.smtp.ssl.enable

Use SSL (true/false), defaults to false .

mail.smtp.timeout

Socket I/O timeout value in milliseconds. Default is infinite timeout.

mail.smtp.username

Specify username if using authentication