

Part

Property Summary

	#allowBreakAcrossPageBounds
Boolean	When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.
	#background
String	The background color of the form part.
	#discardRemainderAfterBreak
Boolean	When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.
	#groupbyDataProviderIDs
String	For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders.
	#height
Number	The height of a selected part; specified in pixels.
	#pageBreakAfterOccurrence
Number	A page break will be inserted after a specified number of occurrences of a selected part.
	#pageBreakBefore
Boolean	When set, a page break will be inserted before each occurrence of a selected part.
	#partType
Number	The type of this part.
	#restartPageNumber
Boolean	When set, page numbering will be restarted after each occurrence of a selected part.
	#sinkWhenLast
Boolean	When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

Property Details

[allowBreakAcrossPageBounds](#)

When set, the remainder of a selected part that does not fit on the page currently being printed, will not be transported to the next page - it will break where the page ends and continue on the next page.

NOTE: Make sure to set this option when you are printing more than one page per record.

Returns

[Boolean](#)

[background](#)

The background color of the form part.

NOTE: When no background color has been set, the default background color will be determined by the Look and Feel (LAF) that has been selected in Application Preferences.

Returns

[String](#)

[discardRemainderAfterBreak](#)

When set, the remainder of a selected part that is broken due to the page ending will not be printed on the next page - it will be discarded.

Returns

[Boolean](#)

[groupbyDataProviderIDs](#)

For Leading Subsummary or Trailing Subsummary parts, one or more dataproviders can be added as Break (GroupBy) dataproviders. The Leading/Trailing Subsummary parts will be displayed once for each resulted group of data.

Returns

[String](#)

[height](#)

The height of a selected part; specified in pixels.

This height property is the lowerbound as its ending Y value (0 == top of the form).

Returns

[Number](#)

[pageBreakAfterOccurrence](#)

A page break will be inserted after a specified number of occurrences of a selected part.

Returns[Number](#)`pageBreakBefore`

When set, a page break will be inserted before each occurrence of a selected part.

Returns[Boolean](#)`partType`

The type of this part.

Returns[Number](#)`restartPageNumber`

When set, page numbering will be restarted after each occurrence of a selected part.

Returns[Boolean](#)`sinkWhenLast`

When set, the last part on a page (such as a Trailing Grand Summary part) will "sink" to the lowest part of the page when there is free space.

Returns[Boolean](#)