

MenuItem

Constants Summary

Number [#ALIGN_CENTER](#)

Number [#ALIGN_LEFT](#)

Number [#ALIGN_RIGHT](#)

Property Summary

Boolean [#enabled](#)

Object[] [#methodArguments](#)
Set the arguments that can be read by the defined method.

String [#name](#)

Boolean [#selected](#)

String [#text](#)

Method Summary

void [#doClick\(\)](#)
Script the selection (emulate a mouse click) of the item.

Object [#getClientProperty](#)(key)
Gets the specified client property for the element based on a key.

void [#putClientProperty](#)(key, value)
Sets the value for the specified element client property key.

MenuItem [#setAccelerator](#)(key)
Set the accelerator key of the item.

void [#setBackgroundColor](#)(backgroundColor)
Set the background color of the item.

void [#setForegroundColor](#)(foregroundColor)
Set the foreground color of the item.

MenuItem [#setIcon](#)(icon)
Set the icon of the item.

MenuItem [#setMethod](#)(method)
Set the method for the item.

MenuItem [#setMnemonic](#)(key)
Set the mnemonic key of the item.

MenuItem [#setVisible](#)(visible)
Set the item visible.

Constants Details

[ALIGN_CENTER](#)

Replace with description

Returns

[Number](#)

[ALIGN_LEFT](#)

Replace with description

Returns

[Number](#)

[ALIGN_RIGHT](#)

Replace with description

Returns

[Number](#)

Property Details

enabled

Replace with description

Returns

Boolean

methodArguments

Set the arguments that can be read by the defined method.

Returns

Object[]

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor(' #ff0000');

menu.setForegroundColor(' #0000ff');
```

name

Replace with description

Returns

String

selected

Replace with description

Returns

Boolean

text

Replace with description

Returns

String

Method Details

doClick

void **doClick()**

Script the selection (emulate a mouse click) of the item.

Returns

void

Sample

```
// Script the selection (emulate a mouse click) of the item.  
// Clicking a separator will throw an error!  
plugins.window.getMenu(2).getItem(0).doClick();
```

getClientProperty

Object **getClientProperty**(key)

Gets the specified client property for the element based on a key.

Parameters

key

Returns

Object

Sample

```
// Gets the specified client property for the element based on a key.  
// NOTE: Depending on the operating system, a user interface property name may be available.  
var property = plugins.window.getClientProperty('ToolTipText');
```

putClientProperty

void **putClientProperty**(key, value)

Sets the value for the specified element client property key.

Parameters

key

value

Returns

void

Sample

```
// Sets the value for the specified element client property key.  
// NOTE: Depending on the operating system, a user interface property name may be available.  
plugins.window.putClientProperty('ToolTipText', 'some text');
```

setAccelerator

MenuItem **setAccelerator**(key)

Set the accelerator key of the item.

Parameters

key

Returns

MenuItem

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

setBackgroundColor

void **setBackgroundColor**(backgroundColor)

Set the background color of the item.

Parameters

backgroundColor

Returns

void

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

setForegroundColor

void **setForegroundColor**(foregroundColor)

Set the foreground color of the item.

Parameters

foregroundColor

Returns

void

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

setIcon

[MenuItem](#) **setIcon**(icon)

Set the icon of the item.

Parameters

icon

Returns

[MenuItem](#)

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

setMethod

[MenuItem](#) **setMethod**(method)

Set the method for the item.

Parameters

method

Returns

[MenuItem](#)

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

[setMnemonic](#)

[MenuItem](#) **setMnemonic**(key)

Set the mnemonic key of the item.

Parameters

key

Returns

[MenuItem](#)

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```

setVisible

[MenuItem](#) **setVisible**(visible)

Set the item visible.

Parameters

visible

Returns

[MenuItem](#)

Sample

```
var menu = plugins.window.getMenu(2).getItem(0);
// Set the text of the item.
menu.setText("Servoy");
// Set the method for the item.
menu.setMethod(callback);
// Set the arguments that can be read by the defined method. - array elements will be passed as arguments 5, 6
and so on to the callback method
//The first 5 arguments are fixed:
//      [0] item index
//      [1] parent item index
//      [2] isSelected boolean
//      [3] parent menu text
//      [4] menu text
menu.methodArguments = ["a","b"];
// Set the icon of the item.
menu.setIcon("media:///TipOfTheDay16.gif");
// Set the accelerator key of the item.
menu.setAccelerator("meta 4");
// Set the mnemonic key of the item.
menu.setMnemonic("e");
// Enable/disable the item.
menu.setEnabled(false);
// Set the item visible.
menu.setVisible(true);

menu.setBackgroundColor('#ff0000');

menu.setForegroundColor('#0000ff');
```