

DataProviderExport

 Apr 07, 2024 05:04

Supported Clients

SmartClient WebClient NGClient

Methods Summary	
DataProviderExp setFormat(format) or DataProviderExp setHeaderText(headerText) or DataProviderExp setValueList(valuelistName) or	Set format for dataprovider value. Set header text for dataprovider value. Set valuelist to resolve display value for dataprovider.

Methods Details

setFormat(format)

Set format for dataprovider value.

Parameters

[String](#) format the dataprovider format

Returns

[DataProviderExport](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var exporter = plugins.textxport.createExporter(forms.form1.foundset,',';',false);
exporter.addDataProvider('mydate').setFormat('yyyy/dd/MM');
var content = exporter.textExport();
```

setHeaderText(headerText)

Set header text for dataprovider value. If no header text is set and exportHeader is true dataprovider will be used as header text.

Parameters

[String](#) headerText the header text

Returns

[DataProviderExport](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var exporter = plugins.textxport.createExporter(forms.form1.foundset,',';',true);
exporter.addDataProvider('orderid').setHeaderText('Order ID');
var content = exporter.textExport();
```

setValueList(valuelistName)

Set valuelist to resolve display value for dataprovider.

Parameters

[String](#) valuelistName the valuelist name

Returns

[DataProviderExport](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var exporter = plugins.textxport.createExporter(forms.form1.foundset, ';', true);  
exporter.addDataProvider('item_id').setValueList('myvaluelist');  
var content = exporter.textExport();
```