

JS Lib

 Apr 07, 2024 13:09

Supported Clients

SmartClient WebClient NGClient MobileClient

Property Summary

Number Infinity

Number NaN

Object undefined

Numeric value representing infinity.

Value representing Not-a-Number.

The value undefined.

Methods Summary

String	decodeURI(encodedURI)	Decodes a URI previously encoded with <code>encodeURIComponent</code> or another similar routine.
String	decodeURIComponent(encodedURI)	Decodes a URI component previously created by <code>encodeURIComponent</code> or by a similar routine.
String	encodeURI(URI)	Encodes a URI by replacing certain characters with escape sequences.
String	encodeURIComponent(URI)	Encodes a URI component by replacing all special characters with their corresponding UTF-8 escape sequences.
Object	eval(expression)	Evaluates JavaScript code passed as a string.
Boolean	isFinite(n)	Returns true if the given number is a finite number.
void	isNaN(value)	The NaN property indicates that a value is 'Not a Number'.
Boolean	isXMLName(name)	Returns true if the given name can be used as a valid name for an XML element or attribute.
Number	parseFloat(text)	Makes a floating point number from the starting numbers in a given string.
Number	parseInt(text)	Makes an integer from the starting numbers in a given string in the base specified.
Number	parseInt(text, radix)	Makes an integer from the starting numbers in a given string in the base specified.
String	uneval(obj)	Returns the string representation behind a given object.

Property Details

Infinity

Numeric value representing infinity.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

Infinity

NaN

Value representing Not-a-Number.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

NaN

undefined

The value undefined.

Returns

[Object](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

```
undefined
```

Methods Details**decodeURI(encodedURI)**

Decodes a URI previously encoded with encodeURI or another similar routine.

Parameters

[String](#) encodedURI;

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

```
var str = "http://www.mysite.com/my code.asp?name=[cool]";
var encoded = encodeURI(str);
var decoded = decodeURI(encoded);
application.output(encoded);//http://www.mysite.com/my%20code.asp?name=%5bcool%5d
application.output(decoded);//http://www.mysite.com/my code.asp?name=[cool]
```

decodeURIComponent(encodedURI)

Decodes a URI component previously created by encodeURIComponent or by a similar routine.

Parameters

[String](#) encodedURI;

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

```
var str = "my code.asp?name=[cool]";
var encoded = encodeURIComponent(str);
var decoded = decodeURIComponent(encoded);
application.output(encoded); //my%20code.asp%3fname%3d%5bcool%5d
application.output(decoded); //my code.asp?name=[cool]
```

encodeURI(URI)

Encodes a URI by replacing certain characters with escape sequences.

Parameters

[String](#) URI;

Returns

[String](#)

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

```
var str = "http://www.mysite.com/my code.asp?name=[cool]";
var encoded = encodeURI(str);
var decoded = decodeURI(encoded);
application.output(encoded);//http://www.mysite.com/my%20code.asp?name=%5bcool%5d
application.output(decoded);//http://www.mysite.com/my code.asp?name=[cool]
```

encodeURIComponent(URI)

Encodes a URI component by replacing all special characters with their corresponding UTF-8 escape sequences.

Parameters

[String](#) URI;

Returns

[String](#)

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
var str = "my code.asp?name=[cool]";
var encoded = encodeURIComponent(str);
var decoded = decodeURIComponent(encoded);
application.output(encoded); //my%20code.asp%3fname%3d%5bcool%5d
application.output(decoded); //my code.asp?name=[cool]
```

eval(expression)

Evaluates JavaScript code passed as a string. Returns the value returned by the evaluated code.

Parameters

[String](#) expression;

Returns

[Object](#)

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
eval("var x = 2 + 3;");
application.output(x); // prints: 5.0
```

isFinite(n)

Returns true if the given number is a finite number.

Parameters

[Number](#) n;

Returns

[Boolean](#)

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
application.output(isFinite(1)); // prints: true
application.output(isFinite(Infinity)); // prints: false
application.output(isFinite(isNaN)); // prints: false
```

isNaN(value)

The NaN property indicates that a value is 'Not a Number'.

Parameters

[Object](#) value;

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
isNaN( value )
```

isXMLName(name)

Returns true if the given name can be used as a valid name for an XML element or attribute.

Parameters

`String` name;

Returns

`Boolean`

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
application.output(isXMLName("good_name")); // prints: true
application.output(isXMLName("bad name")); // because of the space, prints: false
```

parseFloat(text)

Makes a floating point number from the starting numbers in a given string.

Parameters

`String` text;

Returns

`Number`

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
parseFloat('string')
```

parseInt(text)

Makes a integer from the starting numbers in a given string in the base specified.

Parameters

`String` text;

Returns

`Number`

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
parseInt('0774')
```

parseInt(text, radix)

Makes a integer from the starting numbers in a given string in the base specified.

Parameters

`String` text ;

`Number` radix;

Returns

`Number`

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
parseInt('0774' , 8)
```

uneval(obj)

Returns the string representation behind a given object.

Parameters

[Object](#) obj;

Returns

[String](#)

Supported Clients

SmartClient, WebClient, NGClient, MobileClient

Sample

```
application.output(uneval(isNaN)); // prints something like: function isNaN() { [native code for isNaN, arity=1]
}
```