


servoyDeveloper

 Apr 03, 2024 10:56

Supported Clients

SmartClient WebClient NGClient MobileClient

Methods Summary		
void	<code>openForm(form)</code>	Opens the form <code>FormEditor</code> in the developer.
void	<code>save()</code>	Saves all changes made through the solution model into the workspace.
void	<code>save(override)</code>	Saves all changes made through the solution model into the workspace.
void	<code>save(obj)</code>	Saves just the given form, valuelist, relation or in memory datasource into the developers workspace.
void	<code>save(obj, override)</code>	Saves just the given form, valuelist, relation or in memory datasource into the developers workspace.
void	<code>save(obj, solutionName)</code>	Saves just the given form, valuelist, relation or in memory datasource into the developers workspace.
void	<code>updateInMemDataSource(dataSource, dataset, types)</code>	Updates the given in memory datasource and saves it into the developers workspace.

Methods Details

openForm(form)
Opens the form `FormEditor` in the developer.

Parameters

`Object` form The form name or JSForm object to open in an editor.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

save()
Saves all changes made through the solution model into the workspace.
Please note that this method only saves the new in memory datasources,
if you would like to override the existing ones use `servoyDeveloper.save(true)`.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

save(override)
Saves all changes made through the solution model into the workspace.

Parameters

`Boolean` override Override existing in memory tables.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample

save(obj)
Saves just the given form, valuelist, relation or in memory datasource into the developers workspace.
This must be a solution created or altered form/in memory datasource.

Parameters

`Object` obj The formname, JSForm, JSValueList, JSRelation, datasource name or JSDataSource object to save.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample**save(obj, override)**

Saves just the given form, valuelist, relation or in memory datasource into the developers workspace. This must be a solution created or altered form/in memory datasource.

Parameters

Object obj The formname, JSForm, JSValueList, JSRelation, datasource name or JSDataSource object to save.
Boolean override Override an existing in memory table.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample**save(obj, solutionName)**

Saves just the given form, valuelist, relation or in memory datasource into the developers workspace. This must be a solution created form/in memory datasource.
NOTE: The current method can only be used for new objects.
For existing objects, please use the save method with the override flag set to true.
It is not needed to specify the solution, because the object to be updated will be saved in the right solution.

Parameters

Object obj The formname, JSForm, JSValueList, JSRelation, datasource name or JSDataSource object to save.
String solutionName The destination solution, a module of the active solution.

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample**updateInMemDataSource(dataSource, dataset, types)**

Updates the given in memory datasource and saves it into the developers workspace.

Parameters

Object dataSource datasource name or JSDataSource object to save.
Object dataset the dataset with the update columns
Object types array of the update columns types

Supported Clients

SmartClient,WebClient,NGClient,MobileClient

Sample