

Popup

Method Summary

CheckBox `#addCheckBox([name], [method], [icon], [mnemonic], [enabled], [align])`
Add the Checkbox at the selected index (starting at 0) or add it at the end (empty).

Menu `#addMenu([name], [menu], [icon], [mnemonic], [enabled], [align])`
Add the submenu at the selected index (starting at 0) or add it at the end (empty).

MenuItem `#addMenuItem([name], [method], [icon], [mnemonic], [enabled], [align])`
Add the item at the selected index (starting at 0) or add it at the end (empty).

RadioButton `#addRadioButton([name], [method], [icon], [mnemonic], [enabled], [align])`
Add the Radiobutton at the selected index (starting at 0) or add it at the end (empty).

void `#addRadioGroup()`
Add a Radiogroup for the Radiobuttons.

void `#addSeparator()`
Add the separator at the selected index (starting at 0) or add it at the end (empty).

CheckBox `#getCheckBox(index)`
Get the Checkbox at the selected index (starting at 0).

MenuItem `#getItem(index)`
Get the item at the selected index (starting at 0).

Number `#getItemCount()`
Get the number of items in the menu.

Number `#getItemIndexByText(name)`
Retrieve the index of the item by text.

Menu `#getMenu(index)`
Get the submenu at the selected index (starting at 0).

RadioButton `#getRadioButton(index)`
Get the Radiobutton at the selected index (starting at 0).

void `#removeAllItems()`
Remove all items from the menu.

void `#removeItem(index 1, [index 2-n])`
Remove the item(s) at the selected index/indices.

void `#show([element], [x], [y])`
Show the popup below the element or add x an y values relative to the element

Method Details

addCheckBox
CheckBox `addCheckBox([name], [method], [icon], [mnemonic], [enabled], [align])`

Add the Checkbox at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[method]
[icon]
[mnemonic]
[enabled]
[align]

Returns

CheckBox

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addMenu

[Menu](#) **addMenu**([name], [menu], [icon], [mnemonic], [enabled], [align])

Add the submenu at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[menu]
[icon]
[mnemonic]
[enabled]
[align]

Returns

[Menu](#)

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addMenuItem
MenuItem addMenuItem([name], [method], [icon], [mnemonic], [enabled], [align])

Add the item at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[method]
[icon]
[mnemonic]
[enabled]
[align]

Returns

MenuItem

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addRadioButton
RadioButton addRadioButton([name], [method], [icon], [mnemonic], [enabled], [align])

Add the Radiobutton at the selected index (starting at 0) or add it at the end (empty).

Parameters

[name]
[method]
[icon]
[mnemonic]
[enabled]
[align]

Returns

RadioButton

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addRadioGroup

void addRadioGroup()

Add a Radiogroup for the Radiobuttons.

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

addSeparator

void addSeparator()

Add the separator at the selected index (starting at 0) or add it at the end (empty).

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

getCheckBox

CheckBox **getCheckBox**(index)

Get the Checkbox at the selected index (starting at 0).

Parameters

index

Returns

CheckBox

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

getItem

MenuItem **getItem**(index)

Get the item at the selected index (starting at 0).

Parameters

index

Returns**MenuItem****Sample**

```

var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}

```

getItemCount**Number getItemCount()**

Get the number of items in the menu.

Returns**Number****Sample**

```

var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}

```

getItemIndexByText**Number getItemIndexByText(name)**

Retrieve the index of the item by text.

Parameters

name

Returns

Number

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

getMenu

Menu getMenu(index)

Get the submenu at the selected index (starting at 0).

Parameters

index

Returns

Menu

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

getRadioButton

RadioButton **getRadioButton**(index)

Get the Radiobutton at the selected index (starting at 0).

Parameters

index

Returns

RadioButton

Sample

```
var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}
```

removeAllItems

void **removeAllItems()**

Remove all items from the menu.

Returns

void

Sample

```

var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}

```

removeItemvoid **removeItem**(index 1, [index 2-n])

Remove the item(s) at the selected index/indices.

Parameters

index 1

[index 2-n]

Returns

void

Sample

```

var popupmenu = plugins.window.createPopupMenu()

var menuitem1 = popupmenu.addMenuItem('A',myMethod)
var menuitem2 = popupmenu.addRadioButton('B',myMethod)
var menuitem3 = popupmenu.addRadioButton('C',myMethod)
var menuitem4 = popupmenu.addSeparator()
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)

var submenu = popupmenu.addMenu('SubMenu')
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null, 'm') //last parameter is mnemonic-key

menuitem2.setSelected(true);
menuitem6.setEnabled(false)
subitem2.setSelected(true);

var source = event.getSource()
if (source != null)
{
    popupmenu.show(source);
    //or you can set the coordinates popupmenu.show(10, 10);
}

```

show

```
void show([element], [x], [y])  
Show the popup below the element or add x an y values relative to the element
```

Parameters

[element]

[x]

[y]

Returns

void

Sample

```
var popupmenu = plugins.window.createPopupMenu()  
  
var menuitem1 = popupmenu.addMenuItem('A',myMethod)  
var menuitem2 = popupmenu.addRadioButton('B',myMethod)  
var menuitem3 = popupmenu.addRadioButton('C',myMethod)  
var menuitem4 = popupmenu.addSeparator()  
var menuitem5 = popupmenu.addMenuItem('<html><b>Hello</b></html>',myMethod)  
var menuitem6 = popupmenu.addMenuItem('G', globals.myGlobalMethod)  
  
var submenu = popupmenu.addMenu('SubMenu')  
var subitem1 = submenu.addCheckBox('i18n:bla_bla',myMethod)  
var subitem2 = submenu.addCheckBox('he' , globals.myOtherGlobalMethod , 'media:///day_obj.gif')  
var subitem3 = submenu.addCheckBox('more' , globals.myOtherGlobalMethod ,null , 'm') //last parameter is  
mnemonic-key  
  
menuitem2.setSelected(true);  
menuitem6.setEnabled(false)  
subitem2.setSelected(true);  
  
var source = event.getSource()  
if (source != null)  
{  
    popupmenu.show(source);  
    //or you can set the coordinates popupmenu.show(10, 10);  
}
```