

# ValueList

## Property Summary

|         |                                                                                                                                                                                             |
|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number  | <a href="#">#addEmptyValue</a><br>Property that tells if an empty value must be shown next to the items in the value list.                                                                  |
| String  | <a href="#">#customValues</a><br>A string with the elements in the valuelist.                                                                                                               |
| String  | <a href="#">#dataSource</a><br>Compact representation of the names of the server and table that are used for loading the data from the database.                                            |
| String  | <a href="#">#name</a><br>The name of the value list.                                                                                                                                        |
| String  | <a href="#">#relationName</a><br>The name of the relation that is used for loading data from the database.                                                                                  |
| String  | <a href="#">#separator</a><br>A String representing the separator that should be used when multiple display dataproviders are set, when the value list has the type set to database values. |
| String  | <a href="#">#sortOptions</a><br>Sort options that are applied when the valuelist loads its data from the database.                                                                          |
| Boolean | <a href="#">#useTableFilter</a><br>Flag that tells if the name of the valuelist should be applied as a filter on the 'valuelist_name' column when retrieving the data from the database.    |
| Number  | <a href="#">#valueListType</a><br>The type of the valuelist.                                                                                                                                |

## Property Details

[addEmptyValue](#)  
Property that tells if an empty value must be shown next to the items in the value list.

### Returns

[Number](#)

[customValues](#)  
A string with the elements in the valuelist. The elements can be separated by linefeeds (custom1 custom2), optional with realvalues ((custom1|1 custom2|2)).

### Returns

[String](#)

[dataSource](#)  
Compact representation of the names of the server and table that are used for loading the data from the database.

### Returns

[String](#)

[name](#)  
The name of the value list.

It is relevant when the "useTableFilter" property is set.

### Returns

[String](#)

[relationName](#)  
The name of the relation that is used for loading data from the database.

### Returns

[String](#)

[separator](#)  
A String representing the separator that should be used when multiple display dataproviders are set, when the value list has the type set to database values.

### Returns

[String](#)

[sortOptions](#)  
Sort options that are applied when the valuelist loads its data from the database.

### Returns

[String](#)

useTableFilter

Flag that tells if the name of the valuelist should be applied as a filter on the 'valuelist\_name' column when retrieving the data from the database.

**Returns**

Boolean

valueListType

The type of the valuelist. Can be either custom values or database values.

**Returns**

Number