

JSProgressMonitor



Apr 04, 2024 04:03

Supported Clients

SmartClient WebClient NGClient

Methods Summary

Boolean	cancel()	Cancels the transfer process.
Number	getCurrentBytesToTransfer()	Returns the number of bytes to transfer for the current file.
Number	getCurrentFileIndex()	Returns the index of the current file being transferred.
Number	getCurrentTransferredBytes()	Returns the number of bytes already transferred for the current file.
String	getCurrentTransferredFileName()	Returns the name of the current file being transferred.
Number	getTotalBytesToTransfer()	Returns the total bytes to transfer to or from the server (sum of all the files size)
Number	getTotalFilesToTransfer()	Returns the total number of files to transfer.
Number	getTotalTransferredBytes()	Returns the total bytes already transferred (for all files)
Boolean	isCanceled()	Returns true if the process was canceled.
Boolean	isFinished()	Returns true if the process is finished.
JSProgressMonitor or	setProgressCallBack(function, interval)	Sets a method to be called repeatedly at the given interval (in seconds), the method will receive an instance of this JSProgressMonitor updated with the latest values.
JSProgressMonitor or	setProgressCallBack(function, interval, delay)	Sets a method to be called repeatedly at the given interval (in seconds), the method will receive an instance of this JSProgressMonitor updated with the latest values.

Methods Details

cancel()

Cancels the transfer process.

Returns

[Boolean](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
monitor.cancel();
```

getCurrentBytesToTransfer()

Returns the number of bytes to transfer for the current file.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}
```

getCurrentFileIndex()

Returns the index of the current file being transferred.

Returns[Number](#)**Supported Clients**

SmartClient, WebClient, NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

getCurrentTransferredBytes()

Returns the number of bytes already transferred for the current file.

Returns[Number](#)**Supported Clients**

SmartClient, WebClient, NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

getCurrentTransferredFileName()

Returns the name of the current file being transferred.

Returns[String](#)**Supported Clients**

SmartClient, WebClient, NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

getTotalBytesToTransfer()

Returns the total bytes to transfer to or from the server (sum of all the files size)

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}
```

getTotalFilesToTransfer()

Returns the total number of files to transfer.

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}
```

getTotalTransferredBytes()

Returns the total bytes already transferred (for all files)

Returns

[Number](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

isCanceled()

Returns true if the process was canceled.

Returns

[Boolean](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

isFinished()

Returns true if the process is finished.

Returns

[Boolean](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```

application.output('total transferred: ' + monitor.getTotalTransferredBytes() + ' / ' + monitor.
getTotalBytesToTransfer());
application.output('current file: ' + monitor.getCurrentTransferredFileName() + ' ( ' + monitor.
getCurrentFileIndex() + ' / ' + monitor.getTotalFilesToTransfer() + ' )');
application.output('current bytes transferred: '+monitor.getCurrentTransferredBytes() + ' / ' + monitor.
getCurrentBytesToTransfer());
if (monitor.isCanceled()) {
    application.output('canceled!')
}
if (monitor.isFinished()) {
    application.output('finished!')
}

```

setProgressCallback(function, interval)

Sets a method to be called repeatedly at the given interval (in seconds), the method will receive an instance of this JSProgressMonitor updated with the latest values. Can use an optional delay (for testing purpose in developer).

Parameters

[Function](#) function the Function to call back at the specified interval

[Number](#) interval the interval (in seconds) to use

Returns

[JSProgressMonitor](#) this for chaining

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
// call the progressCallbackFuntion every 2 and a half seconds (with a delay of 200ms in developer):  
monitor.setProgressCallBack(progressCallbackFunction, 2.5, (application.isInDeveloper() ? 200 : 0));
```

setProgressCallBack(function, interval, delay)

Sets a method to be called repeatedly at the given interval (in seconds), the method will receive an instance of this JSProgressMonitor updated with the latest values. Can use an optional delay (for testing purpose in developer).

Parameters

[Function](#) function the Function to call back at the specified interval

[Number](#) interval the interval (in seconds) to use

[Number](#) delay adds a delay for testing purpose in Developer

Returns

[JSProgressMonitor](#) this for chaining

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
// call the progressCallbackFuntion every 2 and a half seconds (with a delay of 200ms in developer):  
monitor.setProgressCallBack(progressCallbackFunction, 2.5, (application.isInDeveloper() ? 200 : 0));
```