

QBLogicalCondition

 Apr 04, 2024 22:22

Supported Clients

SmartClient WebClient NGClient

Property Summary

QBTableClause parent
QBSelect root

Get query builder parent table clause, this may be a query or a join clause.
Get query builder parent.

Methods Summary

QBLogicalConditio
on

add(condition)

Add a condition to the AND or OR condition list.

Property Details

parent

Get query builder parent table clause, this may be a query or a join clause.

Returns

QBTableClause

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.person.createSelect();
query.where.add(query.joins.person_to_parent.joins.person_to_parent.columns.name.eq('john'))
foundset.loadRecords(query)
```

root

Get query builder parent.

Returns

QBSelect

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var subquery = datasources.db.example_data.order_details.createSelect();

var query = datasources.db.example_data.orders.createSelect();
query.where.add(query
    .or
        .add(query.columns.order_id.not.isin([1, 2, 3]))
        .add(query.exists(
            subquery.where.add(subquery.columns.orderid.eq(query.columns.order_id)).
root
        ))
    )

foundset.loadRecords(query)
```

Methods Details

add(condition)

Add a condition to the AND or OR condition list.

Parameters

[QBCondition](#) condition the condition to add

Returns

[QBLogicalCondition](#)

Supported Clients

SmartClient, WebClient, NGClient

Sample

```
var query = datasources.db.example_data.orders.createSelect();
query.where.add(query.columns.orderdate.isNull)
```