

JSRecord

Property Summary

[JSFoundSet](#) [foundset](#)
Returns parent foundset of the record.

Method Summary

[String](#) [getDataSource\(\)](#)
Returns the records datasource string.

[Object\[\]](#) [getPKs\(\)](#)
Returns an array with the primary key values of the record.

[Boolean](#) [isEditing\(\)](#)
Returns true or false if the record is being edited or not.

[Boolean](#) [isNew\(\)](#)
Returns true if the current record is a new record or false otherwise.

[void](#) [revertChanges\(\)](#)
Reverts the in memory outstanding (not saved) changes of the record.

Property Details

foundset

Returns parent foundset of the record.

Returns

[JSFoundSet](#) - The parent foundset of the record.

Sample

```
var parent = record.foundset;
```

Method Details

getDataSource

[String](#) [getDataSource\(\)](#)

Returns the records datasource string.

Returns

[String](#) - The datasource string of this record.

Sample

```
var ds = record.getDataSource();
```

getPKs

[Object\[\]](#) [getPKs\(\)](#)

Returns an array with the primary key values of the record.

Returns

[Object\[\]](#) - an Array with the pk values.

Sample

```
var pks = foundset.getSelectedRecord().getPKs() // also foundset.getRecord can be used
```

isEditing

Boolean **isEditing ()**

Returns true or false if the record is being edited or not.

Returns

Boolean - a boolean when in edit.

Sample

```
var isEditing = foundset.getSelectedRecord().isEditing() // also foundset.getRecord can be used
```

isNew

Boolean **isNew ()**

Returns true if the current record is a new record or false otherwise.

Returns

Boolean - true if the current record is a new record, false otherwise;

Sample

```
var isNew = foundset.getSelectedRecord().isNew();
```

revertChanges

void **revertChanges ()**

Reverts the in memory outstanding (not saved) changes of the record.

Returns

void

Sample

```
var record= forms.customer.foundset.getSelectedRecord();  
record.revertChanges();
```