

QBTableClause

 Apr 04, 2024 08:42

Supported Clients

SmartClient WebClient NGClient

Property Summary		
QBColumns	columns	Get all the columns of the datasource that can be used for this query (select or where clause)
QBJoins	joins	Get the joins clause of this table based clause.
QBTableClause	parent	Get query builder parent table clause, this may be a query or a join clause.
QBSelect	root	Get query builder parent.

Methods Summary		
QBColumn	getColumn(name)	Get a column from the table.
QBColumn	getColumn(columnTableAlias, name)	Get a column from the table with given alias.
String	getDataSource()	Returns the datasource for this.
String	getTableAlias()	Returns the table alias for this.

Property Details

columns
Get all the columns of the datasource that can be used for this query (select or where clause)

Returns

[QBColumns](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = foundset.getQuery();
query.result.add(query.columns.name, "name");
query.where.add(query.columns.orderdate.isNull)
```

joins
Get the joins clause of this table based clause.
Joins added to this clause will be based on this table clauses table.

Returns

[QBJoins](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
foundset.getQuery().joins
```

parent
Get query builder parent table clause, this may be a query or a join clause.

Returns

[QBTableClause](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var query = datasources.db.example_data.person.createSelect();
query.where.add(query.joins.person_to_parent.joins.person_to_parent.columns.name.eq('john'))
foundset.loadRecords(query)
```

root

Get query builder parent.

Returns

[QBSelect](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var subquery = datasources.db.example_data.order_details.createSelect();

var query = datasources.db.example_data.orders.createSelect();
query.where.add(query
    .or
        .add(query.columns.order_id.not.isin([1, 2, 3]))
        .add(query.exists(
            subquery.where.add(subquery.columns.orderid.eq(query.columns.order_id)).
root
        ))
    )

foundset.loadRecords(query)
```

Methods Details**getColumn(name)**

Get a column from the table.

Parameters

[String](#) name the name of column to get

Returns

[QBColumn](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
foundset.getQuery().getColumn('orderid')
```

getColumn(columnTableAlias, name)

Get a column from the table with given alias.

The alias may be of the main table or any level deep joined table.

Parameters

[String](#) columnTableAlias the alias for the table

[String](#) name the name of column to get

Returns

[QBColumn](#)

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
foundset.getQuery().getColumn('orderid', 'opk')
```

getDataSource()

Returns the datasource for this.

Returns

[String](#) the dataSource

Supported Clients

SmartClient,WebClient,NGClient

SampleA horizontal rectangular box with rounded ends, intended for sample code.**getTableAlias()**

Returns the table alias for this.

Returns

[String](#) the tableAlias

Supported Clients

SmartClient,WebClient,NGClient

SampleA horizontal rectangular box with rounded ends, intended for sample code.