FormPopup

Feb 22, 2024 07:10

Supported Clients

NGClient

Methods Summary

Object	component()	Get the component form popup will be shown relative to.
void	component(component)	Set component form popup will be shown relative to.
String	dataprovider()	Get the popup form dataprovider (which was set using setter).
void	dataprovider(dataprovider)	Set form popup dataprovider that will be set.
Number	height()	Get the popup form height (which was set using setter).
void	height(height)	Set form popup height.
Object	scope()	Get the popup form scope (which was set using setter).
void	scope(scope)	Set form popup scope that will be modified.
void	show()	Show form popup using parameters that were set
Boolean	showBackdrop()	Get the popup form show backdrop (which was set using setter).
void	showBackdrop(showBackdrop)	Set whether backdrop will be shown.
Number	width()	Get the popup form width (which was set using setter).
void	width(width)	Set form popup width.
Number	x()	Get the popup form x location (which was set using setter).
void	x(x)	Set form popup x location.
Number	y()	Get the popup form y location (which was set using setter).
void	y(y)	Set form popup y location.

Methods Details

component()

Get the component form popup will be shown relative to.

Returns

Object IComponent

Supported Clients

NGClient

Sample

```
popupform.component();
```

component(component)

Set component form popup will be shown relative to. If null, will use coordinates or show at screen center.

Parameters

Object component the form to show

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).component(elements.myelement).show();
```

dataprovider()

Get the popup form dataprovider (which was set using setter).

Returns

String String

Supported Clients

NGClient

Sample

```
popupform.dataprovider();
```

dataprovider(dataprovider)

Set form popup dataprovider that will be set. If this is set, also scope needs to be specified.

Parameters

String dataprovider form popup dataprovider

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).dataprovider('myid').scope(foundset.getSelectedRecord()).
show();
```

height()

Get the popup form height (which was set using setter).

Returns

Number int

Supported Clients

NGClient

Sample

```
popupform.height();
```

height(height)

Set form popup height. If not set, form design height will be used.

Parameters

Number height form popup height

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).height(100).show();
```

scope()

Get the popup form scope (which was set using setter).

Returns

Object Object

Supported Clients

NGClient

Sample

```
popupform.scope();
```

scope(scope)

Set form popup scope that will be modified. If this is set, also dataprovider needs to be specified.

Parameters

Object scope form popup scope to modify

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).dataprovider('myid').scope(foundset.getSelectedRecord()).
show();
```

show()

Show form popup using parameters that were set

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).x(100).y(100).width(100).height(100).showBackdrop(true).show();
```

showBackdrop()

Get the popup form show backdrop (which was set using setter).

Returns

Boolean boolean

Supported Clients

NGClient

Sample

```
popupform.showBackdrop();
```

showBackdrop(showBackdrop)

Set whether backdrop will be shown. Default value is false.

Parameters

Boolean showBackdrop form popup showBackdrop

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).showBackdrop(true).show();
```

width()

Get the popup form width (which was set using setter).

Returns

Number int

Supported Clients

NGClient

Sample

```
popupform.width();
```

width(width)

Set form popup width. If not set, form design width will be used.

Parameters

Number width form popup width

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).width(100).show();
```

x()

Get the popup form x location (which was set using setter).

Returns

Number int

Supported Clients

NGClient

Sample

```
popupform.x();
```

x(x)

Set form popup x location. The priority sequence for location is: related element, set location, center of screen.

Parameters

Number x form popup x location

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).x(100).show();
```

y()

Get the popup form y location (which was set using setter).

Returns

Number int

Supported Clients

NGClient

Sample

```
popupform.y();
```

y(y)

Set form popup y location. The priority sequence for location is: related element, set location, center of screen.

Parameters

Number y form popup y location

Supported Clients

NGClient

Sample

```
plugins.window.createFormPopup(forms.orderPicker).y(100).show();
```