RuntimeContainer

Feb 28, 2024 23:12

Supported Clients

NGClient

Methods Summary

Boolean	addStyleClasses(classes)	Adds one or more style classes to this container.
Boolean	hasStyleClasses(classes)	returns true if this container has all the classes give.
void	removeCSSStyle(key)	Removes a css style that was previously added.
Boolean	removeStyleClasses (classes)	Removes one or more style classes to this container.
void	setCSSStyle(key, value)	Sets a css style to the container.

Methods Details

addStyleClasses(classes)

```
Adds one or more style classes to this container.
```

Parameters

Array classes one or more class names

Returns

Boolean

Supported Clients

NGClient

Sample

hasStyleClasses(classes)

```
returns true if this container has all the classes give.
```

Parameters

Array classes one or more class names

Returns

Boolean

Supported Clients

NGClient

Sample

removeCSSStyle(key)

```
Removes a css style that was previously added.
```

Parameters

String key css key to remove

Supported Clients

NGClient

Sample

removeStyleClasses(classes)

```
Removes one or more style classes to this container.
```

Parameters

Array classes one or more class names

Returns

Boolean

Supported Clients

NGClient

Sample

setCSSStyle(key, value)

Sets a css style to the container.

Parameters

String key css key to add
String value css value to add

Supported Clients

NGClient

Sample