

CSSPosition



Apr 03, 2024 21:15

Supported Clients

NGClient

Property Summary

String	bottom	Get/Set bottom css position (in pixels or percent).
String	height	Get/Set height css position (in pixels or percent).
String	left	Get/Set left css position (in pixels or percent).
String	right	Get/Set right css position (in pixels or percent).
String	top	Get/Set top css position (in pixels or percent).
String	width	Get/Set width css position (in pixels or percent).

Methods Summary

CSSPosition b(bottom)	Set bottom css position (in pixels or percent).
CSSPosition h(height)	Set height css position (in pixels or percent).
CSSPosition l(left)	Set left css position (in pixels or percent).
CSSPosition r(right)	Set right css position (in pixels or percent).
CSSPosition t(top)	Set top css position (in pixels or percent).
CSSPosition w(width)	Set width css position (in pixels or percent).

Property Details

bottom

Get/Set bottom css position (in pixels or percent).

Returns

String

Supported Clients

NGClient

Sample

```
comp.cssPosition.bottom
```

height

Get/Set height css position (in pixels or percent).

Returns

String

Supported Clients

NGClient

Sample

```
comp.cssPosition.height
```

left

Get/Set left css position (in pixels or percent).

Returns

String

Supported Clients

NGClient

Sample

```
var left = comp.cssPosition.left;
```

right

Get/Set right css position (in pixels or percent).

Returns

[String](#)

Supported Clients

NGClient

Sample

```
comp.cssPosition.right
```

top

Get/Set top css position (in pixels or percent).

Returns

[String](#)

Supported Clients

NGClient

Sample

```
comp.cssPosition.top
```

width

Get/Set width css position (in pixels or percent).

Returns

[String](#) width css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.width
```

Methods Details

b(bottom)

Set bottom css position (in pixels or percent).

Parameters

[String](#) bottom bottom position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.r("10").b("10").w("20%").h("30px")
```

h(height)

Set height css position (in pixels or percent).

Parameters

[String](#) height height position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.l("10").t("10").w("20%").h("30px")
```

l(left)

Set left css position (in pixels or percent).

Parameters

[String](#) left left position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.l("10").t("10").w("20%").h("30px")
```

r(right)

Set right css position (in pixels or percent).

Parameters

[String](#) right right position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.r("10").b("10").w("20%").h("30px")
```

t(top)

Set top css position (in pixels or percent).

Parameters

[String](#) top top position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.l("10").t("10").w("20%").h("30px")
```

w(width)

Set width css position (in pixels or percent).

Parameters

[String](#) width width position in pixels or percentage

Returns

[CSSPosition](#) css position

Supported Clients

NGClient

Sample

```
comp.cssPosition.l("10").t("10").w("20%").h("30px")
```