

Component

 Apr 20, 2024 01:05

Supported Clients

SmartClient WebClient NGClient

Methods Summary		
Object	<code>getClientProperty(key)</code>	Gets the specified client property for the element based on a key.
Object	<code>getDesignProperties()</code>	Get the design-time properties of an element.
Object	<code>getDesignTimeProperty(key)</code>	Get a design-time property of an element.
String	<code>getElementType()</code>	Returns the type of a specified element.
String	<code>getFormName()</code>	Returns the name of the form.
String	<code>getName()</code>	Returns the name of an element.
void	<code>putClientProperty(key, value)</code>	Sets the value for the specified element client property key.

Methods Details

getClientProperty(key)
Gets the specified client property for the element based on a key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

Object key user interface key (depends on operating system)

Returns

Object The value of the property for specified key.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var property = %%elementName%%.getClientProperty('ToolTipText');
```

getDesignProperties()
Get the design-time properties of an element.

Returns

Object

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var prop = forms.orders.elements.mylabel.getDesignProperties()
```

getDesignTimeProperty(key)
Get a design-time property of an element.

Parameters

String key the name of the property

Returns

Object

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var prop = forms.orders.elements.mylabel.getDesignTimeProperty('myprop')
```

getElementType()

Returns the type of a specified element.

Returns

[String](#) The display type of the element as String.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var et = %%elementName%%.getElementType();
```

getFormName()

Returns the name of the form. (may be empty string as well)

Returns

[String](#) The name of the form.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var name = %%elementName%%.getFormName();
```

getName()

Returns the name of an element. (may be null as well)

Returns

[String](#) The name of the element.

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
var name = %%elementName%%.getName();
```

putClientProperty(key, value)

Sets the value for the specified element client property key.

NOTE: Depending on the operating system, a user interface property name may be available.

Parameters

[Object](#) key user interface key (depends on operating system)

[Object](#) value a predefined value for the key

Supported Clients

SmartClient,WebClient,NGClient

Sample

```
%%elementName%%.putClientProperty('ToolTipText','some text');
```